



Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

Date of Preparation: 10/11/2016 Date of Revision: 11/27/2017 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Number : 30323
Product Name : Porsche Red Acrylic Enamel

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier
MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Classification

Flammable Liquids - Category 3
Skin Corrosion/Irritation - Category 2
Serious Eye Damage/Eye Irritation - Category 2B
Acute Toxicity, Inhalation - Category 4
Specific Target Organ Toxicity, Single Exposure, R - Category 3
Germ Cell Mutagenicity - Category 2
Carcinogenicity - Category 1A, 1B
Reproductive Toxicity - Category 2
Specific Target Organ Toxicity, Repeated Exposure - Category 2

2.2 Signal Word

DANGER!

2.3 Pictograms



Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

2.4 Hazard Statements

| | |
|------|--|
| H226 | Flammable liquid and vapor |
| H315 | Causes skin irritation |
| H320 | Causes eye irritation |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H341 | Suspected of causing genetic defects |
| H350 | May cause cancer |
| H361 | Suspected of damaging fertility or the unborn child |
| H373 | Causes damage to organs through prolonged or repeated exposure |

2.5 Precautionary Statements

| | |
|--------------|---|
| P201 | Obtain special instructions before use. |
| P202 | Do not handle until all safety precautions have been read and understood. |
| P210 | Keep away from heat/sparks/open flames/hot surface - No smoking. |
| P233 | Keep container tightly closed. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion-proof electrical/ventilating/light/equipment, etc. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray. |
| P264 | Wash hands thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P281 | Use personal protective equipment as required. |
| P302+352 | IF ON SKIN: Wash with soap and water. |
| P303+361+353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so - continue rinsing. |
| P308+313 | IF exposed or concerned: get medical advice/attention. |
| P312 | Call a POISON CENTER or a doctor/physician if you feel unwell. |
| P314 | Get medical advice/attention if you feel unwell. |
| P332+313 | If skin irritation occurs: get medical advice/attention. |
| P337+313 | If eye irritation persists get medical advice/attention. |
| P362 | Take off contaminated clothing and wash before reuse. |
| P370+378 | In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction. |
| P403+233 | Store in a well ventilated place. Keep container tightly closed. |
| P403+235 | Store in a well ventilated place. Keep cool. |
| P405 | Store locked up. |
| P501 | Dispose of contents/container to an approved waste disposal plant. |

Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

SECTION 3: Composition/Information on ingredients

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| MATERIAL | CAS # | WEIGHT % |
|--|------------|----------|
| 2-Propanone | 67-64-1 | 1-5 |
| Iso Butanol | 78-83-1 | 1-5 |
| Stoddard Solvnt | 8052-41-3 | 5-10 |
| Solvent Naphtha (petroleum), light aliphatic | 64742-89-8 | 25-30 |
| Dimethylbenzene | 1330-20-7 | 15-20 |

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION 4: First aid measures

4.1 Contact with Eyes

Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

4.2 Skin Contact

Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

4.3 Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

4.4 Ingestion

If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing Media

Water fog, foam, dry chemical, or carbon dioxide extinguisher.

5.2 Special Fire Fighting Procedures

Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

5.3 Unusual Fire Fighting Hazards

Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

SECTION 6: Accidental release measures

6.1 Personal Precautions

Keep all sources of ignition and hot metal surfaces away from spill or release.

6.2 Environmental Precautions

Contain spill if it can be done with minimal risk. Prevent liquid from entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

6.3 Methods for Cleaning Up

Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

SECTION 7: Handling and storage

7.1 Handling and Storage

"Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1 Exposure Limits

| MATERIAL | CAS # | OSHA PEL | ACGIH TLV |
|--|------------|----------|-----------|
| 2- Propanone | 67-64-1 | 750 ppm | 500 ppm |
| Iso Butanol | 78-83-1 | 100 ppm | 50 ppm |
| Stoddard Solvent | 8052-41-3 | 500 ppm | 100 ppm |
| Solvent Naphtha (petroleum), light aliphatic | 64742-89-8 | 500 ppm | 300 ppm |
| Dimethylbenzene | 1330-20-7 | 100 ppm | 100 ppm |

8.2 Engineering Controls

Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

8.3 Monitoring

Follow accepted work practices for handling a flammable material.

8.4 Personal Protective Equipment

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistant gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas & vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | |
|----------------------------|---|-------------------|
| Appearance | : | Red |
| Odor | : | Mild |
| Odor Threshold | : | No data available |
| pH@25°C | : | Not Applicable |
| Melting/Freezing Point | : | No data available |
| Flash Point | : | -4 °F |
| Specific Gravity (water=1) | : | .92 |
| Water Solubility | : | Negligible |
| Auto-Ignition Temperature | : | No data available |
| Decomposition Temperature | : | No data available |
| Boiling Range | : | 134-281.3°F |
| Evaporation Rate | : | Slower than Ether |
| Lower Flammable Limit | : | 1% |
| Upper Flammable Limit | : | 7% |
| Vapor Pressure | : | 6.44mm Hg@68°F |
| Vapor Density (air=1) | : | >1.0 |
| Viscosity | : | No data available |
| VOC as Packaged | : | 4.10 |
| VOC Regulatory | : | 4.30 |

SECTION 10: Stability and reactivity

10.1 Stability

Stable under normal conditions of storage and handling.

10.2 Conditions to Avoid

Heat, open flames, ignition sources, electrical or static discharge.

10.3 Hazardous Decomposition/Byproducts

CO₂ and possibly CO and carbon smoke.

10.4 Hazardous Polymerization

Will not occur.

10.5 Polymerization Conditions to Avoid

None.

10.6 Incompatibilities

None known.

Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

SECTION 11: Toxicological information

11.1 Likely Route of Exposure

Inhalation, eye contact, skin contact, ingestion.

11.2 Inhalation

Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

11.3 Eye Contact

High vapor concentrations are irritating to the eyes.

11.4 Skin Contact

Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

11.5 Ingestion

Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

11.6 Toxicity

| MATERIAL | LD50 | LC50 |
|--|---|----------------------------------|
| 2- Propanone | Dermal: 20,000 mg/kg (rabbit) Oral: 5.340 mg/kg (rabbit) | Inhalation: 2,100 ppm (cat) |
| Iso Butanol | Dermal: 3,400 mg/kg (rabbit) Oral: 2,460 mg/kg (rat) | Inhalation: 4 h 8,000 ppm (rat) |
| Stoddard Solvent | Not Established | Not Established |
| Solvent Naphtha (petroleum), light aliphatic | Dermal: >4,000 mg/kg (rat) Oral: >8,000 mg/kg (rat) | Inhalation: 4 h 3,400 ppm (rat) |
| Dimethylbenzene | Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat) | Inhalation: 4 h 6,350 mg/l (rat) |

SECTION 12: Ecological information

12.1 Ecotoxicity

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section Xi (Toxicological Information) for further data on the effects of this product's components on test animals.

12.2 Mobility

This material is a mobile liquid.

12.3 Degradability

This product is completely biodegradable.

12.4 Bioaccumulation

This product does not accumulate or biomagnify in the environment.

SECTION 13: Disposal considerations

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

Candy Red Acrylic Enamel (ONT.500-20)

Safety Data Sheet ONT.500-20

SECTION 14: Transport information

14.1 DOT Shipping Information

| | |
|------------------------|--------------------------------|
| PROPER SHIPPING NAME | PAINT |
| CONTAINS | See Section III - Composition/ |
| HAZARD CLASS AND LABEL | 3 FLAMMABLE LIQUID |
| IDENTIFICATION NUMBER | UN1263 |
| PACKAGING GROUP | II |

SECTION 15: Regulatory information

15.1 SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION

ACUTE : Yes

CHRONIC : No

FIRE : Yes

PRESSURE : No

REACTIVE : No

15.2 SARA TITLE III SECTION 313 SUPPLIER INFORMATION

| COMPONENT NAME | CAS # | % BY WT. |
|-----------------|-----------|----------|
| Dimethylbenzene | 1330-20-7 | 15-20 |

15.3 CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE

| COMPONENT NAME | CAS # | % BY WT. | RQ (LBS.) |
|-----------------|-----------|----------|-----------|
| 2- Propanone | 67-64-1 | 1-5 | 5000 |
| Dimethylbenzene | 1330-20-7 | 15-20 | 100 |

15.4 California Proposition 65

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

HMIS Health: 2

HMIS Flammability: 3

HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention as necessary or appropriate to use and understand the data in this SDS.