



# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet ONT.65

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/11/2015 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 2K FAST ACTIVATOR (Part No. 65)  
Product group : 2K Hardener

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

MCGEHEE & MCGEHEE ENTERPRISES INC  
120 SOUTH BOGGESS AVENUE  
KY 42345 - GREENVILLE  
USA  
T (270) 338-4600 - F (270) 338-4602

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Skin Sens. 1 H317  
STOT SE 3 H336  
STOT SE 3 H335  
STOT RE 2 H373

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS07



GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking  
P261 - Avoid breathing fume, spray, vapors  
P264 - Wash hands thoroughly after handling  
P280 - Wear face protection, protective clothing, protective gloves  
P302+P352 - If on skin: Wash with plenty of water  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
HEXAMETHYLENE DIISOCYANATE OLIGOMERS	(CAS No) 28182-81-2	< 43	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
xylene	(CAS No) 1330-20-7	23 - 43	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
ethyl methyl ketone	(CAS No) 78-93-3	23 - 43	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
ethylbenzene	(CAS No) 100-41-4	5 - 23	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Solvent naphtha (petroleum), light arom.,		< 5	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Immediately call a poison center or doctor/physician. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes damage to organs.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Protective clothing. Gloves.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing spray, vapors.
- Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain leaking substance. Collect spillage.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

For further information refer to section 13. See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing spray, vapors. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, Lighting equipment equipment.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Ignition sources, Heat sources, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage temperature : < 25 °C
- Storage area : Keep container in a well-ventilated place.
- Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 2K FAST ACTIVATOR (Part No. 65)

ACGIH	Not applicable
OSHA	Not applicable

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethyl methyl ketone (78-93-3)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	300 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

Solvent naphtha (petroleum), light arom.,		
ACGIH	Not applicable	
OSHA	Not applicable	

HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)		
ACGIH	Not applicable	
OSHA	Not applicable	

### 8.2. Exposure controls

Personal protective equipment

: Avoid all unnecessary exposure. Gas mask. Gloves. Protective clothing. Safety glasses.



Materials for protective clothing

: Impermeable clothing.

Hand protection

: Wear protective gloves.

Eye protection

: Chemical goggles or safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Air-fed respiratory protective equipment should be worn when this product is sprayed. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Other information

: Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Colorless
Odor	: aromatic
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point	: No data available
Boiling point	: > 35 °C
Flash point	: 3 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Specific gravity / density	: 0.94 - 0.96 g/cm <sup>3</sup>
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

VOC content - Actual	: 607 g/l
VOC content	: 607 g/l
VOC content - Regulatory	: 607 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>ethylbenzene (100-41-4)</b>	
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
<b>xylene (1330-20-7)</b>	
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (dust, mist)	1.500 mg/l/4h
<b>HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)</b>	
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified

<b>ethylbenzene (100-41-4)</b>	
IARC group	2B - Possibly carcinogenic to humans
<b>xylene (1330-20-7)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful in contact with skin. Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Repeated exposure to this material can result in absorption through skin causing significant health hazard. Harmful in contact with skin. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

<b>2K FAST ACTIVATOR (Part No. 65)</b>	
Persistence and degradability	Not established.
<b>Solvent naphtha (petroleum), light arom.,</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

<b>2K FAST ACTIVATOR (Part No. 65)</b>	
Bioaccumulative potential	Not established.
<b>Solvent naphtha (petroleum), light arom.,</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer	:
Effect on the global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

# 2K FAST ACTIVATOR (Part No. 65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

- Regional legislation (waste) : Disposal must be done according to official regulations.
- Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to Remove waste in accordance with local and/or national regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II
- UN-No.(DOT) : UN1263
- Proper Shipping Name (DOT) : Paint related material including paint thinning, drying, removing, or reducing compound
- Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 150
- DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
- DOT Packaging Bulk (49 CFR 173.xxx) : 242
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
- DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

#### Additional information

- Other information : No supplementary information available.

#### ADR

- Transport document description : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)
- Packing group (ADR) : II

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :

Tunnel restriction code (ADR) : D/E  
LQ : 5I  
Excepted quantities (ADR) : E2

### Transport by sea

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT RELATED MATERIAL  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger

### Air transport

UN-No. (IATA) : 1263  
Proper Shipping Name (IATA) : Paint  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene	CAS No 100-41-4	5 - 23
xylene	CAS No 1330-20-7	23 - 43
hexamethylene-di-isocyanate	CAS No 822-06-0	< 5

#### ethyl methyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not subject to reporting requirements of the United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 5000 lb

#### ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 1000 lb

#### xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 100 lb

#### Solvent naphtha (petroleum), light arom.,

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### HEXAMETHYLENE DIISOCYANATE OLIGOMERS (28182-81-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory



# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2 H319

Skin Sens. 1 H317

STOT SE 3 H335

STOT SE 3 H336

Full text of H-phrases: see section 16

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

##### 15.2.2. National regulations

#### ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

#### ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	54

## SECTION 16: Other information

Other information : None.

# 2K FAST ACTIVATOR (Part No. ONT.65)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long lasting effects

### NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

### NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



*FOR INDUSTRIAL USE ONLY by professional, trained painters.  
Not for sale to or use by the general public.*