



Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

Date of issue: 07/11/2014

Version: 1.0

SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity : Basecoat Reducer Extra Slow
Product Uses : Basecoat Reducer

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier
MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

DANGER!!

2.1 Hazard Statements (CAT = Hazard Category)

(H200s) PHYSICAL: Flammable Liquids (CAT:1)
H224 EXTREMELY FLAMMABLE LIQUID AND VAPOR.
(H300s) HEALTH: Aspiration Hazard (CAT:1)
H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
(H300s) HEALTH: Skin Corrosion/Irritation (CAT:2)
H315 CAUSES SKIN IRRITATION.
(H300s) HEALTH: Serious Eye Damage/Eye Irritation (CAT:2)
H320 CAUSES EYE IRRITATION.
(H300s) HEALTH: Target Organ Toxicity, Single Exposure (CAT:3)
H335 MAY CAUSE RESPIRATORY IRRITATION.
H336 MAY CAUSE DROWSINESS OR DIZZINESS.
(H300s) HEALTH: Target Organ Toxicity, Single Exposure (CAT:2)
H371 MAY CAUSE DAMAGE TO ORGANS.
(H300s) HEALTH: Reproductive Toxicity (CAT:2)
H361 SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.
(H400s) ENVIRONMENT: Hazardous to Aquatic Environment, Acute (CAT:3)
H402 HARMFUL TO AQUATIC LIFE.



Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

2.2 Precautionary Statements

EXPOSURE PREVENTION: STRICT HYGIENE!

PREVENT DISPERSION OF MISTS OR DUST!

AVOID EXPOSURE OF (PREGNANT) WOMEN!

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P210 Keep away from heat/sparks/open flames/hot surfaces — No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P264 Wash with soap & water thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+352 IF ON SKIN: Wash with soap & water.

P304+340 IF INHALED: Remove victim to fresh air & keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present & easy to do - Continue rinsing.

P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.

P332+313 If skin irritation occurs: Get medical advice/attention.

P337+313 If eye irritation persists, get medical advice/attention.

P361 Remove/Take off immediately all contaminated clothing.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container to an approved waste disposal plant.

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

SECTION 3: Composition/Information on ingredients

MATERIAL	CAS#	EINECS#	WT%
Light Aliphatic Naphtha	*64742-89-8	-	20-30
n-Butyl Ethanoate	123-86-4	204-658-1	10-20
4-Methylpentan-2-one	108-10-1	203-550-1	5-15
Propanone	67-64-1	200-662-2	0-10
2-Propanol	67-63-0	200-662-7	0-10
Xylenes	1330-20-7	215-535-7	0-10
Heptan-2-one	110-43-0	203-767-1	0-10
Ethyl-3-Ethoxypropionate	763-69-9	212-112-9	0-5
Toluene	108-88-3	203-625-9	0-5
Ethylbenzene	100-41-4	202-849-4	0-5

TRACE COMPONENTS: Trace ingredients (if any) are present in <1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

SECTION 4: First aid measures

4.1 Most Important Symptoms/Effects, Acute and Chronic

See Section 11 for Symptoms/Effects (acute & chronic).

4.2 Eye Contact

For eyes, flush with plenty of water for 15 minutes & get medical attention.

4.3 Skin Contact

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap and water. Wash contaminated clothing before reuse.

4.4 Inhalation

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

4.5 Swallowing

Rinse mouth. Give a slurry of activated charcoal in water to drink.

Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Rest.

Do NOT give liquids to an unconscious or convulsing person.

SECTION 5: Firefighting measures

5.1 Fire & Explosion Preventive Measures

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

5.2 Suitable (& Unsuitable) Extinguishing Media

Use dry powder, AFFF, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.

5.3 Special Protective Equipment & Precautions for Fire Fighters

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots).

5.4 Specific Hazards of Chemical & Hazardous Combustion Products

EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

Closed containers may explode if exposed to extreme heat.

Applying to hot surfaces requires special precautions.

Empty container very hazardous! Continue all label precautions!

SECTION 6: Accidental release measures

6.1 Spill and Leak Response and Environmental Precautions

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area).

6.2 Personal Precautions, Protective Equipment, Emergency Procedures

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

6.3 Environmental Precautions

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

6.4 Methods and Material for Containment & Clean-Up

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. Dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

SECTION 7: Handling and storage

7.1 Precautions for Safe Handling

Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.

Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

7.2 Conditions for Safe Storage, including any Incompatibilities

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone. Keep in fireproof surroundings. Keep separated from strong oxidants, strong acids, strong bases. Keep cool. Do not store above 49 C / 120 F. Keep container tightly closed & upright when not in use to prevent leakage.

7.3 Nonbulk: Containers

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

7.4 Bulk Containers

All tanks and pipelines which contain this material must be labeled. Perform routine maintenance on tanks or pipelines which contain this product. Report all leaks immediately to the proper personnel.

7.5 Tank Car Shipments

Tank cars carrying this product should be loaded and unloaded in strict accordance with tank-car manufacturer's recommendation and all established on-site safety procedures. Appropriate personal protective equipment must be used (see Section 8, Engineering Controls and Personal Protective Equipment.). All loading and unloading equipment must be inspected, prior to each use. Loading and unloading operations must be attended, at all times. Tank cars must be level, brakes must be set or wheels must be locked or blocked prior to loading and unloading. Tank car (for loading) or storage tanks (for unloading) must be verified to be correct for receiving this product and be properly prepared, prior to starting the transfer operations. Hoses must be verified to be in the correct positions, before starting transfer operations. A sample (if required) must be taken and verified (if required) prior to starting transfer operations. All lines must be blown-down and purged before disconnecting them from the tank car or vessel.

7.6 Protective Practices during Maintenance of Contaminated Equipment

Follow practices indicated in Section 6 (Accidental Release Measures). Make certain application equipment is locked and tagged-out safely. Always use this product in areas where adequate ventilation is provided. Collect all reinstates and dispose of according to applicable Federal, State, Provincial, or local procedures.

7.7 Empty Container Warning

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

SECTION 8: Exposure controls/personal protection

8.1 Exposure Limits

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
Light Aliphatic Naphtha	*64742-89-8	-	500 ppm	300 ppm
n-Butyl Ethanoate	123-86-4	204-658-1	150 ppm	150 ppm
4-Methylpentan-2-one	108-10-1	203-550-1	100 ppm	20 ppm A3
Propanone	67-64-1	200-662-2	1000 ppm	500 ppm A4
2-Propanol	67-63-0	200-661-7	400 ppm	200 ppm A4
Xylenes	1330-20-7	215-535-7	100 ppm	100 ppm A4
Heptan-2-one	110-43-0	203-767-1	100 ppm	50 ppm
Ethyl-3-Ethoxypropionate	763-69-9	212-112-9	50 ppm	50 ppm
Toluene	108-88-3	203-625-9	200 ppm	50 ppm A4
Ethylbenzene	100-41-4	202-849-4	100 ppm	100 ppm A3

MATERIAL	CAS#	EINECS#	CEILING	STEL (OSHA/ACGIH)	HAP
Light Aliphatic Naphtha	*64742-89-8	-	None Known	5.3E3 ppm	No
n-Butyl Ethanoate	123-86-4	204-658-1	None Known	200 ppm	No
4-Methylpentan-2-one	108-10-1	203-550-1	None Known	75 ppm	Yes
Propanone	67-64-1	200-662-2	None Known	750 ppm	No
2-Propanol	67-63-0	200-661-7	None Known	400 ppm	No
Xylenes	1330-20-7	215-535-7	None Known	150 ppm	Yes
Toluene	108-88-3	203-625-9	None Known	None Known	Yes
Ethylbenzene	100-41-4	202-849-4	None Known	125 ppm	Yes

In addition, using manufacturer's data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Cumene

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

8.2 Appropriate Engineering Controls

RESPIRATORY EXPOSURE CONTROLS

Airborne concentrations should be kept to lowest levels possible. If vapor, dust or mist is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations, after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown. Maintain airborne contaminant concentrations below exposure limits. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For particulates, a particulate respirator (NIOSH Type N95 or better filters) may be worn. If oil particles (such as: lubricants, cutting fluids, glycerine, and so on) are present, use a NIOSH Type R or P filter. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxiliary positive pressure Self-Contained Breathing Apparatus.

VENTILATION

LOCAL EXHAUST: Necessary

MECHANICAL (GENERAL): Necessary

SPECIAL: None

OTHER: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

8.3 Individual Protection Measures, such as Personal Protective Equipment

EYE PROTECTION:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, chemical splash goggles should be worn, when a higher degree of protection is necessary, use splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

HAND PROTECTION:

Use gloves chemically resistant to this material. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl vinyl alcohol laminate ("EVAL"), Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber ("nitril") or ("NBR"), Polyvinyl chloride ("PVC") or "vinyl", Viton. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

BODY PROTECTION:

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

WORK & HYGIENIC PRACTICES:

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using toilet facilities and at the end of the working period. Provide readily accessible eye wash stations & safety showers. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	: Liquid, Water-White
Odor	: Ketone
Odor Threshold	: Not Available
pH (Neutrality)	: Not Available
Melting Point/Freezing Point	: Not Available
Boiling Range (IBP, 50%, Dry Point)	: 56 126 166°C / 134 259 331°F (*=End Point)
Flash Point (Test Method)	: -16 C / 2 F (TCC) (Lowest Component)
Evaporation Rate (n-Butyl Acetate = 1)	: 0.832
Flammability Classification	: Class I B
Lower Flammable Limit in Air (% by vol)	: 1.5
Upper Flammable Limit in Air (% by vol)	: Not Available
Vapor Pressure (mm of Hg) @ 20 C	: 39.8
Vapor Density (air=1)	: 3.3
Gravity @ 68/68 F / 20/20 C	
Density	: 0.814
Specific Gravity (Water=1)	: 0.816
Pounds/Gallon	: 6.794
Water Solubility	: Appreciable
Partition Coefficient (n-Octane/Water)	: Not Available
Auto Ignition Temperature	: 287 C / 550 F
Decomposition Temperature	: Not Available
Total VOC's (TVOC)*	: 99.9 Vol% / 814.8 g/L / 6.7 Lbs/Gal
Nonexempt VOC's (CVOC)*	: 90.7 Vol % / 741.9 g/L / 6.1 Lbs/Gal
Hazardous Air Pollutants (HAPS)	: 24.3 Wt% / 198.2 g/L / 1.6 Lbs/Gal
Nonexempt VOC Partial Pressure (mm of Hg @ 20 C)	: 0.0
Viscosity @ 20 C (ASTM D445)	: Not Available

* Using CARB (California Air Resources Board Rules).

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

SECTION 10: Stability and reactivity

10.1 Reactivity & Chemical Stability

Stable under normal conditions, no hazardous reactions when kept from incompatibles.

10.2 Possibility of Hazardous Reactions & Conditions to Avoid

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

10.3 Incompatible Materials

The substance can presumably form explosive peroxides, under the influence of light and air.

Check for peroxide prior to distillation, eliminate if found.

Reacts violently with strong oxidants, strong reducing agents, strong acids, strong bases, causing fire & explosion hazard. Attacks many plastics, rubber, coatings.

10.4 Hazardous Decomposition Products

Carbon Monoxide, Carbon Dioxide from burning.

10.5 Hazardous Polymerization

Will not occur.

SECTION 11: Toxicological information

11.1 Acute Hazards

11.1.1 EYE & SKIN CONTACT

Primary irritation to skin, defatting, dermatitis.

Absorption thru skin increases exposure.

Primary irritation to eyes, redness, tearing, blurred vision.

Liquid can cause eye irritation. Wash thoroughly after handling.

11.1.2 INHALATION

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause harm to affected organs by routes of entry. Use of alcoholic beverages enhances the harmful effect.

11.1.3 SWALLOWING

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

The symptoms of chemical pneumonitis may not show up for a few days.

11.2 Subchronic Hazards/Conditions Aggravated

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this Document can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

11.3 Chronic Hazards

11.3.1 CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS

Pregnant women should avoid use. May cause birth defects.

Potential Cancer Hazard based on tests with laboratory animals using Methyl Isobutyl Ketone & Ethylbenzene.

Overexposure may create cancer risk.

Leukemia been reported in humans from Benzene.

This product contains less than 49 ppm of Benzene.

Not considered hazardous in such low concentrations.

Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus.

Depending on degree of exposure, periodic medical examination is indicated.

Some persons may be more sensitive to the substance's effect on blood cells.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

11.3.2 TARGET ORGANS

May cause damage to target organs, based on animal data.

11.3.3 IRRITANCY

Irritating to contaminated tissue.

11.3.4 SENSITIZATION

No component is known as a sensitizer.

11.3.5 MUTAGENICITY

No known reports of mutagenic effects in humans.

11.3.6 EMBRYOTOXICITY

No known reports of embryo toxic effects in humans.

11.3.7 TERATOGENICITY

No known reports of teratogenic effects in humans.

11.3.8 REPRODUCTIVE TOXICITY

No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

11.4 Mammalian Toxicity Information

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
n-Butyl Acetate	123-86-4	204-658-1	LOWEST KNOWN LC50 (VAPORS) 2000 ppm (Rats)

SECTION 12: Ecological information

12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION

12.2 Effect of Material on Plants and Animals

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

12.3 Effect of Material on Aquatic Life

The most sensitive known aquatic group to any component of this product is:

Flatworm .032 ppm or mg/L (96 hour exposure).

Keep out of sewers and natural water supplies.

The substance is toxic to aquatic organisms.

12.4 Mobility in Soil

This material is a mobile liquid.

12.5 Degradability

This product is partially biodegradable.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

12.6 Accumulation

This product does not accumulate or biomagnify in the environment.

SECTION 13: Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE USED CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001

SECTION 14: Transport information

IF > 1273 LB / 578 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF XYLENES. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

MARINE POLLUTANT	No
DOT/TDG SHIP NAME	UN1263, Paint Related Material (Contains: Light Aliphatic Naphtha, Xylene), 3, PG-II
DRUM LABEL	(FLAMMABLE LIQUID)
IATA/ICAO	UN1263, Paint Related Material (Contains: Light Aliphatic Naphtha, Xylene), 3, PG-II
IMO/IMDG	UN1263, Paint Related Material (Contains: Light Aliphatic Naphtha, Xylene), 3, PG-II
EMERGENCY RESPONSE GUIDEBOOK NUMBER	128



SECTION 15: Regulatory information

15.1 EPA Regulation

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG.SECTION)	RQ (LBS)
n-Butyl Acetate	123-86-4	204-658-1	10-20	(311, 312)	5000
*Methyl Isobutyl Ketone	108-10-1	203-550-1	5-15	(311, 312, 313, RCRA)	5000
Acetone	67-64-1	200-662-2	0-10	(311, 312)	5000
*Xylenes	1330-20-7	215-535-7	0-10	(311, 312, 313, RCRA)	100
*Toluene	108-88-3	203-625-9	0-5	(311, 312, 313, RCRA)	1000
*Ethylbenzene	100-41-4	202-849-4	0-5	(311, 312, 313, RCRA)	1000

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

15.2 State Regulations

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains the following chemicals known to the State of California to cause cancer: Methyl Isobutyl Ketone, Ethylbenzene

This product contains the following chemical known to the State of California to cause reproductive toxicity: Toluene

15.3 International Régulations

The identified components of this product are listed on the chemical inventories of the following countries:

Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS), Japan (METI/CSCl, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC), Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

15.4 Canada: Workplace Hazardous Materials Information System (WHMIS)

B2: Flammable Liquid.

D2A: Contains a substance known to cause serious chronic toxicity or death. Ethylbenzene.

D2B: Irritating to eyes/skin.

This product was classified using the hazard criteria of the Controlled Products Regulations (CPR). This Document contains all information required by the CPR.

SECTION 16: Other information

16.1 Hazard Ratings

HEALTH (NFPA): 2, HEALTH (HMIS): 2, FLAMMABILITY: 3, PHYSICAL HAZARD: 0

(Personal Protection Rating to be supplied by user based on use conditions.)

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

16.2 Employee Training

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

16.3 SDS Date

07/11/2014

Basecoat Reducer - Extra Slow (ONT.6195)

Safety Data Sheet ONT.6195

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources.

While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.