



On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

Date of issue: 02/16/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name : Activator
Recommended Use : A paint or paint constituent product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier
MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Overall Nature

HAZARDOUS MIXTURE, DANGEROUS GOODS

2.2 Classification Reference SANS10234 (1272/2008/EC)

Classification of the substance or mixture
(H226) Flammable liquids, Hazard Category 3
(H332) Acute Toxicity (inhalation), Hazard Category 4
(H316) Skin Corrosion/Irritation, Hazard Category 3
(H334) Sensitization ^ Respiration, Hazard Category 1
(H351) Carcinogenicity, Hazard Category 2

2.3 GHS Label Elements, including Precautionary Statements

2.3.1 SIGNAL WORD

Danger

2.3.2 PICTOGRAMS



On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

2.3.3 HAZARD AND PRECAUTIONARY STATEMENTS

Hazard Statements:

Flammable liquid and vapor
Harmful if inhaled
Causes mild skin irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
Suspected of causing cancer

Precautionary Statements:

PREVENTION STATEMENTS

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment — if the explosive is electrostatically sensitive.
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.
In case of inadequate ventilation wear respiratory protection.

Response Statements:

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER or doctor/physician if you feel unwell.
If skin irritation occurs: Get medical advice/attention.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
In case of fire: Use powder/ ... for extinction.

Storage Statements:

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal Statements:

Dispose of contents/container in accordance with local/regional/national/international regulations in accordance with local/regional/national/international regulation.

SECTION 3: Composition/Information on ingredients

3.1 Product Type

Mixture

3.2 Generic Name

PAINT or PAINT RELATED MATERIAL

3.3 CAS No.

Not applicable

3.4 EU Index No

Not applicable

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

3.5 UN No

1263

3.6 HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

NAME	% m/m	EC Labels	CAS Number	EC Index
n-BUTYL ACETATE	10-30%		123-86-4	607-025-00-1
ETHYL-3-ETHOXYPROPIONATE	5-10%	-	000763-69-9	
TOLUENE DI-ISOCYANATE MIXED ISOMERS.	0.1-1.0%	T+	26471-62-5	615-006-00-4
2-BUTOOXY ETHYL ACETATE	<25%	Xn	112-07-2	607-038-00-2
AROMATIC HYDROCARBON	<20%	Xn		o
XYLENE	<12.5%	Xn	1330-20-7	601-022-00-9

3.7 Classification Reference SANS10234 (1272/2008/EC)

EC INDEX	CLASSIFICATION	HAZARD CODE
607-025-00-1	Flam. Liq. 3; STOT SE 3	H226; H336
615-006-00-4	Carc. 2; Acute Tox. 2; Eye Irrit. 2; STOT SE 3; Skin Irrit. 2; Resp. Sens. 1; Skin Sens. 1; Aquatic Chronic 3	H351; H330; H319; H335; H315; H334; H317; H412
607-038-00-2	Acute Tox. 2; Acute Tox. 4	H332; H312 I o not found in T31 I
601-022-00-9	Flam. Liq. 3; Acute Tox. 4; Acute Tox. 4; Skin Irrit. 2	H226; H332; H312; H315

SECTION 4: First aid measures

4.1 Inhalation

Move to fresh air. In case of any discomfort seek medical attention immediately.

4.2 Skin

Use hand cleaner/soap and water. Remove contaminated clothing. If any discomfort get medical attention.

4.3 Eyes

ACT FAST! Rinse immediately with plenty of water. Refer immediately to Doctor.

4.4 Ingestion

Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing Media

Foam. CO2. Dry Powder. Fog to cool and control. Do NOT use water jets.

5.2 Specific Hazards Arising from the Chemical

Containers can burst in a fire. Can form explosive vapor/air mixture. Static discharge hazard!

Flammable with toxic fumes.

Cool containers in case of fire.

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

5.3 Special Protective Actions for Fire-Fighters

Suitable extinguishing media: Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential.

Prevent, by any means available, spillage from entering drains or water courses.

SECTION 6: Accidental release measures

Contain and collect. Use an inert - NOT sawdust. Keep out of drains and sewers.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation.

SECTION 7: Handling and storage

7.1 Storage

Store separately from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards).

No open flames. No smoking.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

7.2 Handling

Ensure good ventilation/exhaustion at the workplace

Do not spray on a naked flame or any incandescent material

Eating, drinking and smoking in work areas is prohibited

Wash hands after use

Remove contaminated clothing and protective equipment before entering eating area

7.3 Inhalation

Use respiratory protection. Handle with extreme care. Absorb any spillage at once.

7.4 Skin

Avoid direct contact. Use barrier cream and impervious gloves.

7.5 Eyes

Use goggles. Avoid direct contact.

7.6 Ingestion

Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8: Exposure controls/personal protection

8.1 Hazardous and/or Other Relevant Components

NAME	CAS NUMBER	TWA OEL (mg/m ³)	TWA OEL (ppm)	STOEL (mg/m ³)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
ACTIVATOR	Not applicable						
Components	---	---	---	---	---	---	---
n-BUTYL ACETATE	123-86-4	710	150	950	200	RL	8.7
ETHYL-3-ETHOXYPR OPIONATE	000763-69-9		50		100		2.0

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

NAME	CAS NUMBER	TWA OEL (mg/m3)	TWA OEL (ppm)	STOEL (mg/m3)	STOEL (ppm)	OEL Type	Vap.Press. (mmHg)
TOLUENE DI-ISOCYANATE MIXED ISOMERS	26471-62-5			0.070		CL S	0.01
2-BUTOXY ETHYL ACETATE	112-07-2						
XYLENE	1330-20-7	435	100	650	150	RL+S	6.7

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

8.2 OEL Type: Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary

Appropriate hand protection and protective clothing must always be used

Keep away from foodstuffs, beverages and feed

Wash hands before breaks and at the end of work

8.3 Paint Type

Mixture of synthetic resins, pigments and solvents

8.4 General PPE Requirements

For Mixing, Brush Application, Roller Application, Pouring, etc.

8.5 Personal Protective Equipment

SKIN PPE: Overall and impervious gloves (e.g. nitrile rubber)

RESPIRATORY PPE: Air purifying respirator (e.g. cartridge type)

EYE PPE: Face shield or solvent resistant goggles

8.6 HMIS Rating (USA)

2 - 3 - 0 - 1 (Health - Flam - Reactivity - PPE)

8.7 SAPMA Rating

2-H-E PPE: Gloves, Respirator and Eye Protection



8.8 SPRAY BOOTH

SPRAY BOOTH TYPE: Spray booth complying with National Standards

SKIN PPE: Nitrile Gloves

EYES PPE: Face shield or solvent resistant goggles

RESPIRATORY PROTECTION: Air supplied full face piece or head covering respirator suitable for organic vapors/particulates

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	: Viscous Liquid
Odor	: Pungent
pH	: No data available
Boiling point	: >35°C
Melting point	: No data available
Flash Point	: >23°C
Explosive prop	: No data available
Oxidizing prop	: No data available
Vapor Pressure	: No data available
Density	: No data available
Water Solubility	: No data available
Fat Solubility	: No data available
Partition coefficient	: No data available
Viscosity	: No data available
Vapor density	: No data available
Evaporation Rate	: No data available
Auto Ignition Temperature	: No data available
L.E.L.	: No data available
U.E.L.	: No data available
% non volatile	: No data available
Regulatory VOC	: 4.31 lbs./gal (517 g/L)
Actual VOC	: 4.31 lbs./gal (517 g/L)

SECTION 10: Stability and reactivity\

Stable under normal conditions

Prone to ignite by static

No reaction with fire-fighting water

Keep away from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

SECTION 11: Toxicological information

NAME	CAS NUMBER	LD50 ORAL mg/kg	LD50 SKIN mg/kg	LC50 INHAL (GAS) ppmV	LC50 INHAL (MIST) mg/ft
Activator	Not applicable	>500			
Components:	--	--	--	--	--
n-BUTYL ACETATE	123-86-4	14000 mg (Rat)	>5000 mg (Rabbit)		
ETHYL-3- ETHOXYPROPIO NATE	000763-69-9	>500 mg (Rat)			
TOLUENE DI- ISOCYANATE MIXED ISOMERS	26471-62-5	6170 mg (Rat)			
2-BUTOXY ETHYL ACETATE	112-07-2	3200 mg (Mouse)	1580 mg (Rat)		
XYLENE	1330-20-7	4300 mg (Rat)	5000 mg (Rabbit)		
Inhalation				HARMFUL. Contains ISOCYANATE. Sensitizer with accumulative effects.	
Skin				HARMFUL BY CONTACT.	
Eyes				Highly Irritating and risk of irreversible damage.	
Ingestion				Harmful if swallowed. Can affect CNS. Systemic poison.	

SECTION 12: Ecological information

May have short term environmental effects. Contain, monitor and remove

12.1 Aquatic Toxicity

No further relevant information available.

12.2 Persistence and Degradability

No further relevant information available.

12.3 Bioaccumulative Potential

No further relevant information available.

12.4 Mobility in Soil

No further relevant information available.

12.5 Available Ecological Data of Ingredients

NAME	CAS #	AQUATIC TOXICITY
XYLENE	1330-20-7	LC50 (goldfish) = 13 mg/L; 24 hr
		LC50 (rainbow trout) = 13.5 mg/L; 96 hr
		EC50 Daphnia magna 3.82 mg/L; 48 hr

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

SECTION 13: Disposal considerations

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14: Transport information

UN Number	1263
Shipping Name	PAINT or PAINT RELATED MATERIAL
IMO Class	3.3
Packing Group	III
Action Code	127
HazChem	3[Y]
Kemler Code	30
USA (DOT)	UN1263
CANADA (TDG)	UN1263



SECTION 15: Regulatory information

15.1 Canadian DSL Inventory

Components are listed on inventory list

15.2 USA TSCA Inventory

Components are listed on inventory list

15.3 CANADA

WHMIS:

B-2: Flammable liquid with Flash Point lower than 37.8°C (100°F)

D-2B: Material causing other toxic effects

SECTION 16: Other information

CONTAINS ISOCYANATE - POTENTIAL SENSITIZER - ENSURE PRECAUTIONS ARE TAKEN.

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

PAY SPECIAL ATTENTION TO STORAGE AND HANDLING REQUIREMENTS.

HMIS Rating (USA): 2 - 3 - 0 - I (Health - Flam - Reactivity - PPE)

Hazard (H) phrases associated with components

H226 : Flammable liquid and vapor

H312 : Harmful in contact with skin

H315 : Causes skin irritation

H317 : May cause an allergic skin reaction

H319 : Causes serious eye irritation

H330 : Fatal if inhaled

H332 : Harmful if inhaled

H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 : May cause respiratory irritation

H336 : May cause drowsiness or dizziness

H351 : Suspected of causing cancer

H412 : Harmful to aquatic life with long lasting effects

On Track Refinish G2G Activator SLOW (ONT.1185)

Safety Data Sheet ONT.1185

Abbreviations

Code : Abbreviation : Meaning

- : flammable

T+ : very toxic

Xn : harmful

=====
: :

: : Associated pictogram code shown in brackets

H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3

H312 : Acute Tox. 4 : (GHS07) Acute toxicity (dermal), Hazard Category 4

H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2

H317 : Skin Sens. 1 : (GHS07) Sensitization ^ Skin, Hazard Category 1

H319 : Eye Dam/Irrit 2 : (GHS07) Serious eye damage/eye irritation, Hazard Category 2

H330 : Acute Tox. 1 : (GHS06) Acute toxicity (inhalation), Hazard Category 1

H332 : Acute Tox. 4 : (GHS07) Acute toxicity (inhalation), Hazard Category 4

H334 : Resp. Sens. 1 : (GHS08) Sensitization ^ Respiration, Hazard Category 1

H335 : STOT SE 3 : (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation

H336 : STOT SE 3 : (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Narcosis

H351 : Carc. 2 : (GHS08) Carcinogenicity, Hazard Category 2

H412 : Aquatic Chronic 3 : (none) Hazardous to the aquatic environment ^ Chronic Hazard, Category 3

=====
: :

: %m/m : Percent by mass

: ACGIH : American Conference of Governmental Industrial Hygienist

: ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service

: CHIP : Chemicals (Hazard Information and Packaging for supply)

: CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

: CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardization

: DOT : Department of Transport

: EC : European Community

: EC50 : Effective Concentration (Median) for 50% of the response under test

: ECB : European Chemicals Bureau

: ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)

: EEC : European Economic Community

: EINECS : European Inventory of Existing Chemical Substances

: ELINCS : European List of Notified Chemical Substances

: GHS : Globally Harmonized System of Classification and Labelling of Chemicals

: HMIS : Hazardous Materials Information System (USA only)

: IATA : International Air Transport Association

: IMDG : International Maritime Dangerous Goods Code

: IMO : International Maritime Organization

: INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007

: ISO : International Standards Organization

: L.E.L. : Lower explosive limit

: LD50/LC50 : Median (50%) lethal dose/concentration

: mg/m3 : Milligrams per cubic meter

: MSDS : Material safety data sheet

: n/a. : Not available

: NC : No Classification

: No : Number

: OEL : Occupational exposure limit

: OEL-CL : Occupational exposure limit - control limit

: OEL-RL : Occupational exposure limit - recommended limit

: OHS Act : Occupational Health and Safety Act

: P statement : Precautionary statement

: PEL : Permissible Exposure Limit

: PPE : Personal protective equipment

: ppm : Parts per million

: REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals

: RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)

: SABS : South African Bureau of Standards

: SANS : South African National Standards

: SAPMA : South African Paint Manufacturers Association

: SARA 313 : Toxic Release Inventory Reporting SRA Section 3

: SDS : Safety Data Sheet

: STOEL : Short-term occupational exposure limit

: STOT-RE : Specific Target Organ Toxicity - Repeated Exposure

: STOT-SE : Specific Target Organ Toxicity - Single Exposure

: TDG : Transport of Dangerous Goods

: TSCA : Toxic Substance Control Act (USA only)

: TWA : Time weighted average

: U.E.L. : Upper explosive limit

: UN : United Nations

: WHMIS : Workplace Hazardous Materials Information Systems (Canada only)

=====
: :

This SDS conforms with General Administrative Regulations of 6 Sept.1996 (SANS11014:2010/ISO11014:2009)

OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of issue: 02/16/2015 Date of revision: 07/20/2016)