



On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

Date of issue: 04/01/2015 Revision Date: 06/16/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	:	A-6020 Black Chip Guardian
Product Description	:	Rocker Guard Coating, Black, Aerosol
General Use	:	Aerosol Coating, Automotive Use Only
Chemical Family	:	Organic Coating
Molecular Formula	:	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 GHS Classifications

Health:

Eye Irritation, Category 2
Skin Irritation, Category 2
Target Organ Toxicity (Single Exposure), Category 3
Target Organ Toxicity (Repeated Exposure), Category 2
Reproductive Toxicity, Category 2
Carcinogenicity, Category 2

Physical:

Flammable Aerosols, Category 1
Gases Under Pressure
Simple Asphyxiant, Category 1

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

2.2 GHS Label

Hazardous components for labelling:

Acetone, Toluene and Carbon Black



2.3 Signal Word

Danger

2.4 Hazard Statements

- H222: Extremely flammable aerosol.
- H280: Contains gas under pressure; may explode if heated.
- H319: Causes serious eye irritation.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs (central nervous system) through prolonged or repeated exposure.
- H361: Suspected of damaging fertility or the unborn child.
- H351: Suspected of causing cancer.
- H600: May displace oxygen and cause rapid suffocation.

2.5 Precautionary Statements

Prevention:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211: Do not spray on an open flame or other ignition source.
- P251: Do not pierce or burn, even after use.
- P264: Wash hands thoroughly after handling.
- P260: Do not breathe mist, vapors, or spray.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves and eye protection.

Response:

- P308+P313: IF exposed or concerned: Get medical advice/attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310: Immediately call a POISON CENTER or doctor/physician.
- P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.
- P332+P313: If skin irritation occurs: Get medical advice/attention.
- P362: Take off contaminated clothing.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

- P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P405: Store locked up.

Disposal:

- P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

2.6 Emergency Overview

Immediate Concerns:

Flammable aerosol. Harmful if inhaled. Possible risk of harm to the unborn child. Causes serious eye irritation. Irritating to skin. Vapors may cause drowsiness and dizziness. Vapor reduces oxygen availability for breathing.

2.7 Hazards Not Otherwise Classified

No data available.

2.8 Comments:

20% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See section 12 for more detailed information on environmental effects.

This product is a consumer product and is labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations which take precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling. The actual container label will not include the above label elements. The labeling above applies to products used solely for industrial/professional use.

SECTION 3: Composition/Information on ingredients

CHEMICAL NAME	Wt.%	CAS No.
Acetone	40-45	67-64-1
Toluene	15-20	108-88-3
Propane	12-18	74-98-6
Isobutane	5-8	75-28-5
Carbon Black	0.5-1	1333-86-4

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Eye Contact

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes.

Get medical attention, if irritation persists.

4.2 Skin Contact

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

4.3 Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

4.4 Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

4.5 Signs and Symptoms of Overexposure

4.5.1 Eye Contact:

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

4.5.2 Skin Contact:

Contact causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

4.5.3 Ingestion:

Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

4.5.4 Inhalation:

High gas, vapor, mist or dust concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

4.6 Notes to Physician

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

4.7 Additional Information

No data available.

SECTION 5: Firefighting measures

5.1 Flammable Properties

Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point. Product can be ignited by static discharge.

5.2 Extinguishing Media

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

5.3 Hazardous Combustion Products

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.4 Fire Fighting Procedures

Containers can build up pressure if exposed to heat (fire).

5.5 Fire Fighting Equipment

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

5.6 Sensitivity to Static Discharge

Product is sensitive to static discharge.

5.7 Sensitivity to Mechanical Impact

Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120 °F (49 °C).

SECTION 6: Accidental release measures

6.1 Small Spill

Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

6.2 Environmental Precautions

Water Spill:

Do not flush to sewer.

Land Spill:

Avoid runoff into storm sewers and ditches which lead to waterways.

6.3 Special Protective Equipment

Clean up spills immediately, observing precautions in Protective Equipment section 8.

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

SECTION 7: Handling and storage

7.1 General Procedures

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

7.2 Handling

Contents under pressure. Do not expose to heat or store above 120 °F (49 °C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breath vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

7.3 Storage

Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

SECTION 8: Exposure controls/personal protection

8.1 Exposure Guidelines

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)

Chemical Name		Occupational Exposure Limits					
		OSHA PEL		ACGIH TLV		NIOSH REL	
		ppm	mg/m3	ppm	mg/m3	ppm	mg/m3
Acetone	TWA	1000	2400	500		250	590
	STEL			750		-	-
Toluene	TWA	200		50	188	100	375
	STEL	300				150	560
Propane	TWA	1000	1800	1000		1000	ND
Isobutane	TWA			1000		800	ND
Carbon Black	TWA		3.5		3		ND

8.2 Engineering Controls

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

8.3 Personal Protective Equipment

EYES AND FACE:

Wear safety glasses with side shields (or goggles).

SKIN CONTACT:

Wear chemical resistant gloves.

RESPIRATORY:

NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

PROTECTIVE CLOTHING:

Not applicable for aerosol containers.

8.4 Work Hygienic Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid, without aerosol propellants
Odor	:	Ketone
Odor Threshold	:	No data available
Appearance	:	Aerosol
Color	:	Black
pH	:	Not Applicable
% Volatiles	:	80 to 85 % w/w
Flash Point and Method	:	-18 °C Setflash Closed Cup (Acetone)
Flammable Limits	:	1.0 to 12.8
NOTES: Based on data for acetone		
Autoignition Temperature	:	480 °C
NOTES: Based on data for acetone		
Vapor Pressure	:	50 - 65 psig at 20 °C
Vapor Density	:	> 1 (air = 1)
Boiling Point	:	56 °C (Acetone)
Freezing Point	:	No data available
Melting Point	:	No data available
Solubility in Water	:	Partial
Evaporation Rate (n-Butyl Acetate = 1)	:	> 1
Density	:	0.97 ± 0.02g/ml at 20 °C
Viscosity	:	> 100 cps
VOC Content	:	Summarized below
Partition Coefficient (n-octanol/water)	:	No data available
Oxidizing Properties	:	None

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

9.2 Flammability Statement

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability	Yes
Aerosol Flame Projection	> 15 cm but < 100 cm
Flashback	None

9.3 VOC Compliance Statement

Total Volatiles	< 660 g/l 80 - 85% w/w
VOC Regulation	USA National VOC Emission Standards for Aerosol Coatings - 40 CFR Part 59 SUBPART E
Coating Strategy	Flat Coatings
VOC Content	Product-Weighted Reactivity (PWR): < 1.2 g O ₃ /g product < 40% w/w (< 270 g/l)

The VOC content meets the 1.20 PWR category limit for Flat Coatings. USA compliant.

SECTION 10: Stability and reactivity

10.1 Reactive Hazard

No.

10.2 Hazardous Polymerization

Not expected to occur.

10.3 Stability

Stable.

10.4 Conditions to Avoid

Keep away from flames and any object that sparks. Container may explode if heated.

10.5 Possibility of Hazardous Reactions

Not Available

10.6 Hazardous Decomposition Products

Carbon Monoxide and other toxic vapors.

10.7 Incompatible Materials

Oxidizing Materials.

SECTION 11: Toxicological information

11.1 Product Acute Toxicity

Chemical Name	ORAL LD50 mg/kg (rat)	DERMAL LD50 mg/kg (rabbit)	INHALATION LC50 mg/l
Acetone	8400 5250 (mouse) 5300 (rabbit)	>15,700	50.1 (rat;8h) 44.0 (mouse;4h)

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

Chemical Name	ORAL LD50 mg/kg (rat)	DERMAL LD50 mg/kg (rabbit)	INHALATION LC50 mg/l
Toluene	7000, 6400, 5500	12,270	49.0 (rat;8h) 30.0 (mouse;2h) 19.9 (mouse;7h)
Propane	Not Applicable	Not Applicable	>20,000 ppm (rat,4h)
Isobutane	Not Applicable	Not Applicable	142.5 ppm (rat, 4h)

Acute Toxicity - Dermal LD50: The calculated ATE is >2000 mg/kg.

Notes:

Based on available data, the classification criteria for Acute Dermal Toxicity are not met for this mixture.

Acute Toxicity - Oral LD50: The calculated ATE is >2000 mg/kg.

Notes:

Based on available data, the classification criteria for Acute Oral Toxicity are not met for this mixture.

Acute Toxicity - Inhalation LC50: The calculated ATE is >20 mg/l/4h (vapours) and >5 mg/l/4h (mists).

Notes:

Based on available data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture.

Toxicological Data:

20% of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

11.2 Eye Irritation/Serious Eye Damage

Contains: Acetone. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

11.3 Skin Irritation/Corrosion

Contains: Toluene. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

11.4 Carcinogenicity

Chemical Name	NTP Status	IARC Status	OSHA Status	Other
Acetone	—	—	—	
Toluene	—	3	—	—
Carbon Black	—	2B	—	—

Notes: The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2).

11.5 Specific Target Organ Toxicity - Repeated Exposure

The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Toluene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

11.6 Respiratory / Skin Sensitizer

Based on available data, the classification criteria for skin/respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and <1.0% ingredients classified as a skin/respiratory sensitizer, sub-category 1B).

11.7 Reproductive Toxicity

The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as Reproductive Toxicity, category 2). May cause adverse reproductive effects. Possible risk of harm to the unborn child (Toluene).

11.8 Specific Target Organ Toxicity - Single Exposure

The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ($\geq 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). Contains: Toluene. Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

11.9 Germ Cell Mutagenicity

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and <1.0% ingredients classified as Germ Cell Mutagen, category 2).

11.10 Aspiration Hazard

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture (< 10% ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm²/s at 40°C).

SECTION 12: Ecological information

12.1 Environmental Data

No data available.

12.2 Ecotoxicological Information

No data available.

12.3 Bioaccumulation/Accumulation

No data available.

12.4 Distribution

No data available.

12.5 Aquatic Toxicity (Acute)

No data available.

12.6 Chemical Fate Information

No data available.

SECTION 13: Disposal considerations

13.1 Disposal Method

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

13.2 Product Disposal

When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

SECTION 14: Transport information

DOT (Department of Transportation)

Proper Shipping Name	Aerosols, Flammable
Primary Hazard Class/Division	2.1

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

DOT (Department of Transportation)	
UN/NA Number	1950
Packing Group	N/AP
Other Shipping Information	With an inner packaging <1.0L, this product may be shipped as a Limited Quantity as per DOT 173.306.

Air (ICAO/IATA)	
Shipping Name	Aerosols, Flammable
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
Subsidiary Risk	None
Label	Flammable Gas

Vessel (IMO/IMDG)	
Shipping Name	Aerosols
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
Marine Pollutant	None
Label	None

NOTE: With an inner packaging <1.0 L, this product may be shipped as a Limited Quantity.

Canadian Transportation of Dangerous Goods Regulations	
Shipping Name	Aerosols, Flammable
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
TDG Note:	With an inner packaging <1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

SECTION 15: Regulatory information

15.1 UNITED STATES

SARA Section 311/312 Hazard Categories	
Fire Hazard	Yes

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

SARA Section 311/312 Hazard Categories

Sudden Release of Pressure	Yes
Reactive Hazard	No
Product Acute Toxicity	Yes
Product Chronic Toxicity	Yes

Chemical Name	WT. %	CAS No.
Toluene	15-20	108-88-3

EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status: This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical Name	Wt. %	RQ
Acetone	40-45	5,000
Toluene	15-20	1,000

TSCA (The Toxic Substances Control Act)

TSCA Status: All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) - Hazardous Air Pollutants

Chemical Name	Wt. %	CAS No.
Toluene	15-20	108-88-3

CAA 112 (r) - List of Substances for Accidental Release Prevention:

Name	CAS No.	Threshold Qty (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

California Proposition 65

Chemical Name	Wt. %	Listed
Toluene	15-20	- - Developmental Toxicity - Female Reproductive

OSHA Hazard Communication Standard (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

15.2 CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

Name	CAS No.	NPRI Part No.
Toluene	108-88-3	1A, 5 (VOC)
Propane	74-98-6	5 (VOC)
Butane (all isomers)	75-28-5	5 (VOC)

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments:

VOC Content - See section 9.

SECTION 16: Other information

Reason for Issue: NEW

Approved By: Jim Gordon

Prepared By: Regulatory Compliance

Title: R&D Chemist

Date Revised: 06/16/2015

Information Contact: 905-670-5411

HMIS RATING:

Health: * 2

Flammability: 3

Physical Hazard: 0

Personal Protection: E

NFPA 30 / 30B Storage Classification: Level 2 Aerosol

Manufacturer Supplemental Notes:

None

Data Sources:

Not Available

Additional MSDS Information:

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer


MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Act

NFPA CODES



On Track Chip Guardian (BLACK) (ONT.A-6020)

Safety Data Sheet ONT.A-6020

SARA The Superfund Amendments

WHMIS Workplace Hazardous Materials Information System

GENERAL STATEMENTS:

None

COMMENTS:

None

MANUFACTURER DISCLAIMER:

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.