



Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

Date of issue: 02/13/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Code : 1485
Product Name : Activator
Recommended Use : A paint or paint constituent product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Overall Nature

HAZARDOUS MIXTURE, DANGEROUS GOODS

2.2 Classification Reference SANS10234 (1272/2008/EC)

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

- (H226) Flammable liquids, Hazard Category 3
- (H332) Acute Toxicity (inhalation), Hazard Category 4
- (H315) Skin Corrosion/Irritation, Hazard Category 2
- (H334) Sensitization ^ Respiration, Hazard Category 1
- (H351) Carcinogenicity, Hazard Category 2

2.3 GHS Label Elements, including Precautionary Statements

2.3.1 Signal Word

DANGER

2.3.2 Pictograms



Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

2.4 Hazard and Precautionary Statements

2.4.1 HAZARD STATEMENTS

Flammable liquid and vapor
Harmful if inhaled
Causes skin irritation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
Suspected of causing cancer

2.4.2 PRECAUTIONARY STATEMENTS

PREVENTION STATEMENTS

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment. - if the explosive is electrostatically sensitive.
Use explosion-proof electrical/ventilating/lighting/.../equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash ... thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Use personal protective equipment as required.
In case of inadequate ventilation wear respiratory protection.

2.4.3 RESPONSE STATEMENTS

IF ON SKIN: Wash with plenty of soap and water.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a POISON CENTER or doctor/physician if you feel unwell.
Specific treatment (see ... on this label). ... Reference to supplemental first aid instruction.
If skin irritation occurs: Get medical advice/attention.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
Take off contaminated clothing and wash before reuse.
In case of fire: Use powder/ ... for extinction.

2.4.4 STORAGE STATEMENTS

Store in a well-ventilated place. Keep cool.
Store locked up.

2.4.5 DISPOSAL STATEMENTS

Dispose of contents/container in accordance with local/regional/national/international regulations in accordance with local/regional/national/international regulation.

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

SECTION 3: Composition/Information on ingredients

3.1 Product Type

Mixture

3.2 Generic Name

PAINT or PAINT RELATED MATERIAL

3.3 CAS No

Not Applicable

3.4 EU Index No

Not Applicable

3.5 UN No

1263

3.6 HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

Name	% m/m	EC Labels	CAS Number	EC Index
PENTYL ACETATE	10-30 %	-	628-63-7	607-130-00-2
TOLUENE DI-ISOCYANATE MIXED ISOMERS	0.1-1.0 %	T+	26471-62-5	615-006-00-4
2-METHOXY-1-METHYLETHYL ACETATE	<20 %	-	108-65-6	607-195-00-7
5-METHYLHEXAN-2-ONE	<25 %	- Xn	110-12-3	606-026-00-4
XYELENE	<12.5 %	Xn	1330-20-7	601-022-00-9

3.7 Classification Reference SANS 10234 (1272/2008/EC)

EC Index	Classification	Hazard Code
607-130-00-2	Flam. Liq. 3	H226
615-006-00-4	Carc. 2; Acute Tox. 2; Eye Irrit. 2; STOT SE 3; Skin Irrit. 2; Resp. Sens. 1; Skin Sens. 1; Aquatic Chronic 3	H351; H330; H319; H335; H315; H334; H317; H412
607-195-00-7	Flam. Liq. 3	H226
606-026-00-4	Flam. Liq. 3; Acute Tox. 4	H226; H332
601-022-00-9	Flam. Liq. 3; Acute Tox. 4; Acute Tox. 4; Skin Irrit. 2	H226; H332; H312; H315

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

SECTION 4: First aid measures

4.1 Inhalation

Move to fresh air. In case of any discomfort seek medical attention immediately.

4.2 Skin

Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention.

4.3 Eyes

ACT FAST! Rinse immediately with plenty of water. Refer immediately to Doctor.

4.4 Ingestion

Wash mouth with plenty of water. Do NOT induce vomiting. Seek medical advice.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing Media

Foam. Dry powder. Fog to cool and control. Do NOT use water jets.

5.2 Specific Hazards Arising from the Chemical

Containers can burst in a fire. Can form explosive vapor/air mixture. Static discharge hazard!

Highly flammable with toxic fumes.

Cool containers in case of fire.

5.3 Special Protective Actions for Fire-Fighters

Suitable extinguishing media: Foam, dry agent

Substance reacts violently/is explosive

For fires use breathing apparatus. If no fire, breathing apparatus not essential

Prevent, by any means available, spillage from entering drains or water courses.

SECTION 6: Accidental release measures

Contain & Collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

Wear protective equipment (see Section 8). Keep unprotected persons away.

Do not allow product to reach sewage system or any water course.

Remove ignition sources and provide sufficient ventilation.

SECTION 7: Handling and storage

7.1 Storage

Store separately from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards).

No open flames. No smoking. No sparks.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws.

7.2 Handling

Ensure good ventilation/exhaustion at the workplace.

Do not spray on a naked flame or any incandescent material.

Eating, drinking and smoking in work areas is prohibited.

Wash hands after use.

Remove contaminated clothing and protective equipment before entering eating areas.

7.3 Inhalation

Use respiratory protection. Handle with extreme care. Absorb any spillage at once.

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

7.4 Skin

Avoid direct contact. Use barrier cream and impervious gloves.

7.5 Eyes

Use goggles. Avoid direct contact.

7.6 Ingestion

Observe the rules of hygiene. Wash before eating, drinking or smoking.

SECTION 8: Exposure controls/personal protection

8.1 Hazardous and/or Other Relevant Components

NAME	CAS NUMBER	TWA OEL (mg/m ³)	TWA OEL (ppm)	STOEL (mg/m ³)	STOEL (ppm)	OEL Type	Vap. Press. (mmHg)
ACTIVATOR	Not Applicable	-	-	-	-	-	-
PENTYL ACETATE	628-63-7	532	100	800	150	RL	
TOLUENE DI-ISOCYANATE MIXED ISOMERS.	26471-62-5			0.070		CL S	0.01
2-METHOXY-1-METHYLETHYL ACETATE	108-65-6						
5-METHYLHEXAN-2-ONE	110-12-3	240	50	360	75	RL	
XYLENE	1330-20-7	435	100	650	150	RL+S	6.7

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

8.2 OEL Type: Mixture

Maintain air concentrations below occupational exposure standards, using engineering controls as necessary.

Appropriate hand protection and protective clothing must always be used.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

8.3 Paint Type

Mixture of synthetic resins, pigments and solvents

8.4 General PPE Requirements

For Mixing, Brush Application, Roller Application, Pouring, etc.

8.5 Personal Protective Equipment

8.5.1 Skin PPE

Overall and impervious gloves (e.g. nitrile rubber)

8.5.2 Respiratory PPE

Air purifying respirator (e.g. cartridge type)

8.5.3 Eye PPE

Face shield or solvent resistant goggles

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

8.6 HMIS Rating (USA)

2-3-0-I (Health-Flam-Reactivity-PPE)

8.7 SAPMA Rating

2-H-E PPE: Gloves, Respirator and Eye Protection



8.8 Spray Booth

8.8.1 Spray Booth Type

Spray booth complying with National Standards

8.8.2 Skin PPE

Nitrile Gloves

8.8.3 Eyes PPE

Face shield or solvent resistant goggles

8.8.4 Respiratory Protection

Air supplied full face piece or head covering respirator suitable for organic vapors/particulates.

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Property	: Value
Appearance	: Viscous Liquid
Odor	: Pungent
pH	: not available
Boiling Point	: >35°C
Melting Point	: not available
Flash Point	: >23°C
Explosive Prop	: not available
Oxidizing Prop	: not available
Vapor Pressure	: not available
Density	: not available
Water Solubility	: not available
Fat Solubility	: not available
Partition Coefficient	: not available
Viscosity	: not available
Vapor Density	: not available
Evaporation Rate	: not available
Auto Ignition Temperature	: not available
L.E.L.	: not available
U.E.L.	: not available
% non volatile	: not available
Regulatory VOC	: 3.38 lbs./gal (405 g/L)
Actual VOC	: 3.38 lbs./gal (405 g/L)

SECTION 10: Stability and reactivity

Stable under normal conditions

Could generate static - USE EARTHING

No reaction with fire-fighting water

Keep away from: explosives, toxic gases, oxidizing substances, organic peroxides, poisonous (toxic) substances, infectious substances (biohazards),

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

SECTION 11: Toxicological information

NAME	CAS NUMBER	LD50 ORAL mg/kg	LD50 SKIN mg/kg	LC50 INHAL(GAS) ppmV	LC50 INHAL(MIST) mg/ft
ACTIVATOR	Not applicable	>500			
Components:	-	-	-	-	-
PENTYL ACETATE	628-63-7	7400 mg (Rabbit)			
TOLUENE DI- ISOCYANATE MIXED ISOMERS	26471-62-5	6170 mg (Rat)			
2-METHOXY-1- METHYLETHYL ACETATE	108-65-6				
5- METHYLHEXAN-2 -ONE	110-12-3				
XYELENE	1330-20-7	4300 mg (Rat)	5000 mg (Rabbit)		

11.1 Inhalation

HARMFUL. Contains ISOCYANATE. Sensitizer with accumulative effects.

11.2 Skin

HARMFUL BY CONTACT.

11.3 Eyes

Highly irritating and risk of irreversible damage.

11.4 Ingestion

Irritating.

SECTION 12: Ecological information

May have short term environmental effects. Contain, monitor & remove

AQUATIC TOXICITY: No further relevant information available

PERSISTENCE AND DEGRADABILITY: No further relevant information available

BIOACCUMULATIVE POTENTIAL: No further relevant information available.

MOBILITY IN SOIL: No further relevant information available.

AVAILABLE ECOLOGICAL DATA OF INGREDIENTS:

NAME	CAS NUMBER	AQUATIC TOXICITY
Xylene	1330-20-7	LC50 (goldfish) = 13 mg/l; 24 hr
		LC50 (rainbow trout) = 13.5 mg/L; 96 h
		EC50 Daphnia magna 3.82 mg/L; 48 h

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

SECTION 13: Disposal considerations

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

SECTION 14: Transport information

UN Number	1263
Shipping Name	PAINT or PAINT RELATED MATERIAL
IMO Class	3.3
Packing Group	III
Action Code	127
HazChem	3 [Y]
Kemler Code	30
USA (DOT)	UN1263
CANADA (TDG)	UN1263



SECTION 15: Regulatory information

15.1 CANADIAN DSL INVENTORY

Components are listed on inventory list

15.2 USA TSCA INVENTORY

Components are listed on inventory list

15.3 Canada

WHMIS

B-2	Flammable liquid with Flash Point lower than 37.8°C (100°F)
D-2B	Material causing other toxic effects

SECTION 16: Other information

CONTAINS ISOCYANATE - POTENTIAL SENSITIZER - ENSURE PRECAUTIONS ARE TAKEN.

IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

PAY SPECIAL ATTENTION TO STORAGE AND HANDLING REQUIREMENTS.

HMIS Rating (USA): 2-3-0-1 (Health - Flam-Reactivity-PPE)

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

Hazard (H) Phrases Associated with Components	
H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H412	Harmful to aquatic life with long lasting effects

Abbreviations

Code : Abbreviation : Meaning

- : flammable

T+ : very toxic

Xn : harmful

==== :

.. : Associated pictogram code shown in brackets

H226 : Flam. Liq. 3 : (GHS02) Flammable liquids, Hazard Category 3

H312 : Acute Tox. 4 : (GHS07) Acute toxicity (dermal), Hazard Category 4

H315 : Skin Corr/Irrit. 2 : (GHS07) Skin corrosion/irritation, Hazard Category 2

H317 : Skin Sens. 1 : (GHS07) Sensitization ^ Skin, Hazard Category 1

H319 : Eye Dam/Irrit 2 : (GHS07) Serious eye damage/eye irritation, Hazard Category 2

H330 : Acute Tox. 1 : (GHS06) Acute toxicity (inhalation), Hazard Category 1

H332 : Acute Tox. 4 : (GHS07) Acute toxicity (inhalation), Hazard Category 4

H334 : Resp. Sens. 1 : (GHS08) Sensitization ^ Respiration, Hazard Category 1

H335 : STOT SE 3 : (GHS07) Specific target organ toxicity ^ Single exposure, Hazard Category 3, Respiratory tract irritation

H351 : Carc. 2 : (GHS08) Carcinogenicity, Hazard Category 2

H412 : Aquatic Chronic 3 : (none) Hazardous to the aquatic environment ^ Chronic Hazard, Category 3

==== :

: %m/m : Percent by mass

: ACGIH : American Conference of Governmental Industrial Hygienist

: ATE : Acute Toxicity Estimate

: CAS : Chemical Abstracts Service

: CHIP : Chemicals (Hazard Information and Packaging for supply)

: CLP : Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures

: CNS : Central Nervous System

: DIN : Standard of the German Institute for Standardization

: DOT : Department of Transport

: EC : European Community

: EC50 : Effective Concentration (Median) for 50% of the response under test

: ECB : European Chemicals Bureau

: ECHA : European Chemicals Agency, Helsinki (http://echa.europa.eu/home_en.asp)

: EEC : European Economic Community

: EINECS : European Inventory of Existing Chemical Substances

: ELINCS : European List of Notified Chemical Substances

: GHS : Globally Harmonized System of Classification and Labelling of Chemicals

: HMIS : Hazardous Materials Information System (USA only)

: IATA : International Air Transport Association

: IMDG : International Maritime Dangerous Goods Code

: IMO : International Maritime Organization

: INS : Guidance on Identification and Naming of Substances under REACH, ECHA, 2007

: ISO : International Standards Organization

: L.E.L. : Lower explosive limit

: LD50/LC50 : Median (50%) lethal dose/concentration

: mg/m3 : Milligrams per cubic meter

: MSDS : Material safety data sheet

: n.a. : Not available

: NC : No Classification

: No : Number

: OEL : Occupational exposure limit

: OEL-CL : Occupational exposure limit - control limit

: OEL-RL : Occupational exposure limit - recommended limit

: OHS Act : Occupational Health and Safety Act

: P statement : Precautionary statement

: PEL : Permissible Exposure Limit

: PPE : Personal protective equipment

: ppm : Parts per million

: REACH : Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals

: RTDG : Regulations on the Transport of Dangerous Goods. Generic term that covers all modal transport regulations (ADR, RID, ADN, IMDG and ITDG)

: SABS : South African Bureau of Standards

: SANS : South African National Standards

: SAPMA : South African Paint Manufacturers Association

: SARA 313 : Toxic Release Inventory Reporting SRA Section 3

Gun-It Clearcoat Hardener Slow (ONT.1485)

Safety Data Sheet ONT.1485

: SDS : Safety Data Sheet
: STOEL : Short-term occupational exposure limit
: STOT-RE : Specific Target Organ Toxicity - Repeated Exposure
: STOT-SE : Specific Target Organ Toxicity - Single Exposure
: TDG : Transport of Dangerous Goods
: TSCA : Toxic Substance Control Act (USA only)
: TWA : Time weighted average
: U.E.L. : Upper explosive limit
: UN : United Nations
: WHMIS : Workplace Hazardous Materials Information Systems (Canada only)
: ===== :

This SDS conforms with General Administrative Regulations of 6 Sept. 1996 (SANS11014:2010/ISO11014:2009) OEL's derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug. 1995 (EH-42). All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

While all information is accurate to the best of our knowledge, we continue updating ALL SDS document formats in accordance with the most recent GHS mandated changes.

(Date of Issue: 02/13/2015)

(Date of Revision: 07/20/2016)