

Safety Data Sheet ONT.YZ

Date of Preparation: 06/01/2015 Date of Revision: 09/19/2016 Version: 1.0 SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **Product identifier**

Product name : Ford Oxford White

Product group : Basecoat

1.2. Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet 1.3.

Supplier

MCGEHEE & MCGEHEE ENTERPRISES INC 120 SOUTH BOGGESS AVENUE USA T (270) 338-4600 - F (270) 338-4602

1.4. **Emergency telephone number**

Emergency number 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

Classification

Flammable Liquids - Category 3

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2B

Acute Toxicity, Inhalation - Category 4

Specific Target Organ Toxicity, Single Exposure, R - Category 3

Germ Cell Mutagenicity - Category 2

Carcinogenicity - Category 1A, 1B

Reproductive Toxicity - Category 2

Specific Target Organ Toxicity, Repeated Exposure - Category 2

Signal Word 2.2

DANGER!

2.3 **Pictograms**



Safety Data Sheet ONT.YZ

	,				
2.4	Hazard	Statements			
H226	Flamma	ble liquid and vapor			
H315	Causes	skin irritation			
H320	Causes	eye irritation			
H332	P. Harmful if inhaled				
H335	5 May cause respiratory irritation				
H341	Suspected of causing genetic defects				
H350	May cause cancer				
H361	Suspected of damaging fertility or the unborn child				
H373	Causes damage to organs through prolonged or repeated exposure				
2.5	Precaut	ionary Statements			
P201	Obtain s	special instructions before use.			
P202	Do not h	nandle until all safety precautions have been read and understood.			
P210	Keep av	vay from heat/sparks/open flames/hot surface — No smoking.			
P233	Keep co	intainer tightly closed.			
P240	Ground/bond container and receiving equipment.				
P241	Use explosion-proof electrical/ventilating/light/equipment, etc.				
P242	Use only non-sparking tools.				
P243	Take pre	ecautionary measures against static discharge.			
P260	Do not b	preathe dust/fume/gas/mist/vapors/spray.			
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.				
P264	Wash ha	ands thoroughly after handling.			
P271	Use only	y outdoors or in a well-ventilated area.			
P280		otective gloves/protective clothing/eye protection/face protection.			
P281		sonal protective equipment as required.			
P302+3		IF ON SKIN: Wash with soap and water.			
P303+36		IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.			
P304+34		IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.			
P305+351+338		IF IN EYES: Rinse cautiously with water for several mintues. Remove contact lenses if present and easy to do so — continue rin sing.			
P308+3	13	IF exposed or concerned: get medical advice/attention.			
P312	Call a P	OISON CENTER or a doctor/physician if you feel unwell.			
P314	Get med	dical advice/attention if you feel unwell.			
P332+3	13	If skin irritation occurs: get medical advice/attention.			
P337+3	13	If eye irritation persists get medical advice/attention.			
P362 Take off contaminated clothing and wash before reuse.		· ·			
P370+378		In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction.			
P403+23		Store in a well ventilated place. Keep container tightly closed.			
P403+235		Store in a well ventilated place. Keep cool.			
P405	Store lo	·			
P501	Dispose	of contents/container to an approved waste disposal plant.			

Safety Data Sheet ONT.YZ

SECTION 3: Composition/Information on ingredients

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

MATERIAL	CAS#	WEIGHT %	
Iso Butanol	78-83-1	<1	
Isopropyl Alcohol 99%	67-63-0	1-5	
Methyl AMYL Ketone	110-43-0	15-20	
Stoddard Solvent	8052-41-3	<1	
Butyl Acetate	123-86-4	20-25	
Dimethylbenzene	1330-20-7	15-20	

SEE SECTIONS VIII, XI, XII FOR TOXICOLOGICAL INFORMATION.

SECTION 4: First aid measures

4.1 Contact with Eyes

Flush IMMEDIATELY with copious amounts of running water for at least 15 minutes. Take to physician for definitive medical treatment.

4.2 Skin Contact

Wash exposed areas with water and mild soap. Remove contaminated clothing immediately and launder before reuse. If irritations persist, consult a physician.

4.3 Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing

4.4 Ingestion

If swallowed. Do not induce vomiting. Seek immediate medical attention.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing Media

Water fog, foam, dry chemical, or carbon dioxide extinguisher.

5.2 Special Fire Fighting Procedures

Use self-contained breathing apparatus and full bunker gear in fire areas. Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water used for cooling.

5.3 Unusual Fire Fighting Hazards

Vapor accumulation will flash and/or explode, if ignited. Containers may burst explosively if overheated in fire. Cool with water spray or fog. Empty containers also present fire explosion hazard due to residual vapors. Keep containers tightly closed. During emergency situations, over-exposure to decomposition products may cause a health hazard with no symptoms immediately apparent. Obtain medical attention.

Safety Data Sheet ONT.YZ

SECTION 6: Accidental release measures

6.1 Personal Precautions

Keep all sources of ignition and hot metal surfaces away from spill or release.

6.2 Environmental Precautions

Contain spill if it can be done with minimal risk. Prevent liquid form entering drains, sewers or waterways. Notify proper authorities if spill is in excess of the reportable quantity.

6.3 Methods for Cleaning Up

Using only non-sparking tools and explosion proof equipment, collect spill on absorbent material and put into approved container. Call Chemtrec at 1-800-424-9300 (CCN16851) for additional information.

SECTION 7: Handling and storage

"Empty" containers retain residue and/or vapor and may be dangerous. Do not cut, weld, braze, solder, drill, grind or expose such containers to heat, flames, sparks, or other ignition sources. Keep containers tightly closed when not in use. Store out of direct sunlight and in a cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1 Exposure Limits

PUT A CHART IN HERE

8.2 Engineering Controls

Adequate local or mechanical to reduce vapor or mist to below the PEL or TLV.

8.3 Monitoring

Follow accepted work practices for handling a flammable material.

8.4 Personal Protective Equipment (PPE)

EYE PROTECTION: Goggles or approved OSHA device with side shields; do not wear contact lenses when handling this product.

SKIN PROTECTION: Impervious solvent resistant gloves. Impervious apron and work boots recommend where splashing may occur.

RESPIRATORY PROTECTION: Use NIOSH/MSHA TC23C Chemical/Mechanical type filter system to remove a combination of particles, gas and vapors or air supplied respirator if necessary in areas where the chemical exposure is unknown or above the OSHA PEL or ACGIH TLV.

Safety Data Sheet ONT.YZ

SECTION 9: Physical and chemical properties

White Appearance

Odor Mild

Odor Threshold No data available

pH@25°C Not Applicable

Melting/Freezing Point No data available

Flashpoint °F

Specific Gravity (water=1) 1.18

Water Solubility Negligible

Auto-Ignition Temperature No data available

Decomposition Temperature No data available

Boiling Range -°F

Evaporation Rate Slower than Ether

Lower Flammable Limit 1%

Upper Flammable Limit 7%

Vapor pressure mm HG@68°F

Vapor Density (air=1) >1.0

Viscosity No data available.

VOC as Packaged 5.71 **VOC Regulatory** : 5.71

Safety Data Sheet ONT.YZ

SECTION 10: Stability and reactivity

10.1 Stability

Stable under normal conditions of storage and handling.

10.2 Conditions to Avoid

Heat, open flames, ignition sources, electrical or static discharge.

10.3 Hazardous Decomposition/Byproducts

CO2 and possibly CO and carbon smoke.

10.4 Hazard Polymerization

Will not occur.

10.5 Polymerization conditions to Avoid

None.

10.6 Incompatibilities

None known.

SECTION 11: Toxicological information

11.1 Likely Route of Exposure

Inhalation, eye contact, skin contact, ingestion.

11.2 Inhalation

Anesthetic. Irritation of respiratory tract or acute nervous system depression. Overexposure may result in headaches and nausea possibly followed by loss of consciousness.

11.3 Eye Contact

High vapor concentrations are irritating to the eyes.

11.4 Skin Contact

Liquids can be absorbed through the skin resulting in symptoms similar to the inhalation effects above.

11.5 Ingestion

Gastrointestinal irritation including vomiting can occur. Aspiration of material into lungs may result in chemical pneumonitis, which can be fatal.

11.6 Toxicity

MATERIAL	LD50	LC50	
Iso Butanol	Dermal: 3,400 mg/kg (rabbit) Oral: 2,460 mg/kg (rat)	Inhalation: 4 h 8,000 ppm (rat)	
Isopropyl Alcohol 99%	Dermal: 16,400 mg/kg (rabbit) Oral: 5,840 mg/kg (rat)	Inhalation: 8 h 1,600 ppm (rat)	
Methyl AMYL Ketone	Dermal: >2,000 mg/kg (rat) Oral: 1,600 mg/kg (rat)	Inhalation: 4 h >16.7 mg/l (rat)	
Stoddard Solvent	Not Established	Not Established	
Butyl Acetate	Oral: 7,100 mg/kg (mouse)	Inhalation: 2,000 ppm (rat)	
Dimethylbenzene	Dermal: 4,500 mg/kg (rabbit) Oral: 2,840 mg/kg (rat)	Inhalation: 4 h 6,350 mg/l (rat)	

Safety Data Sheet ONT.YZ

SECTION 12: Ecological information

Ecotoxicity

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section XI (Tocicological Information) for further data on the effects of this product's components on test animals.

12.2 **Mobility**

This material is a mobile liquid.

Degradability

This product is completely biodegradable.

12.4 **Bioaccumulation**

This product does not accumulate or biomagnify in the environment.

SECTION 13: Disposal considerations

Do not discharge into drains, surface water, or groundwater. Empty containers can retain product residue and vapor. Observe all precautions even when containers are empty. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. It is the waste generators responsibility to determine if a particular waste is hazardous under RCRA. Dispose of or incinerate in accordance with all applicable local, state, and federal regulations at a RCRA licensed facility.

SECTION 14: Transport information

DOT SHIPPING INFORMATION

PROPER SHIPPING NAME: PAINT

CONTAINS: SEE SECTIONS III - Composition/ HAZARD CLASS AND LABEL: 3 FLAMMABLE LIQUID

IDENTIFICATION NUMBER: UN1263

PACKAGING GROUP: II

SECTION 15: Regulatory information

SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION

ACUTE: Yes CHRONIC: No FIRE: Yes PRESSURE: No REACTIVE: No

SARA TITLE III SECTION 313 SUPPLIER INFORMATION 15.2

COMPONENT NAME	CAS#	% BY WEIGHT	
Butyl Acetate	123-86-4	20-25	
Demethylbenzene	1330-20-7	15-20	

CERCLA SECTION 102 (a) HAZARDOUS SUBSTANCE 15.3

COMPONENT NAME	CAS#	% BY WT.	RQ(LBS.)
Butyl Acetate	123-86-4	20-25	5000
Dimethylbenzene	1330-20-7	15-20	100

Safety Data Sheet ONT.YZ

CALIFORNIA PROPOSITION 65

This product contains no chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 16: Other information

HMIS Health: 2 HMIS Flammability: 3 HMIS Reactivity: 0

DISCLAIMER: WARNING! KEEP THIS AND ALL PAINT RELATED PRODUCTS OUT OF THE REACH OF CHILDREN! The information contained in this SDS is based on data from sources considered to be reliable but we do not guarantee the accuracy or completeness thereof. We urge each customer or recipient of this SDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology, or fire prevention has necessary or appropriate to use and understand the data in this SDS.