



# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

Date of issue: 02/01/2015

Version: 1.0

### SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements of the Global Harmonizing System.

THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling and disposing of this product.

Pass this information on to employees, customers, and users of this product.

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Identity : 150B Basecoat Balancer

Product Uses : Paint Related Material

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

MCGEHEE & MCGEHEE ENTERPRISES INC

120 SOUTH BOGGESS AVENUE

- USA

T (270) 338-4600 - F (270) 338-4602

### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

## SECTION 2: Hazards identification

### DANGER!!

### 2.1 Hazard Statements: (CAT = Hazard Category)

(H200s) PHYSICAL: Flammable Liquids (CAT:2)

H225 HIGHLY FLAMMABLE LIQUID AND VAPOR.

(H300s) HEALTH: Aspiration Hazard (CAT:1)

H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

(H300s) HEALTH: Skin Corrosion/Irritation (CAT:2)

H315 CAUSES SKIN IRRITATION.

(H300s) HEALTH: Serious Eye Damage/Eye Irritation (CAT:2)

H320 CAUSES EYE IRRITATION.

(H300s) HEALTH: Acute Toxicity, Inhalation (CAT:4)

H332 HARMFUL IF INHALED.

(H300s) HEALTH: Target Organ Toxicity, Single Exposure (CAT:3)

H335 MAY CAUSE RESPIRATORY IRRITATION.

H336 MAY CAUSE DROWSINESS OR DIZZINESS.

(H300s) HEALTH: Target Organ Toxicity, Single Exposure (CAT:2)

H371 MAY CAUSE DAMAGE TO ORGANS.

(H400s) ENVIRONMENT: Hazardous to Aquatic Environment, Acute (CAT:3)

H402 HARMFUL TO AQUATIC LIFE.



# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### 2.2 Precautionary Statements

EXPOSURE PREVENTION: STRICT HYGIENE!

PREVENT DISPERSION OF MISTS OR DUST!

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

- P210 Keep away from heat/sparks/open flames/hot surfaces — No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash with soap and water thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P302+352 IF ON SKIN: Wash with soap and water.
- P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - Continue rinsing.
- P309+311 If exposed or you feel unwell: Call a POISON CENTER or doctor/physician.
- P331 Do NOT induce vomiting.
- P332+313 If skin irritation occurs: Get medical advice/attention.
- P337+313 If eye irritation persists, get medical advice/attention.
- P361 Remove/Take off immediately all contaminated clothing.
- P363 Wash contaminated clothing before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container complying with local/regional/federal regulations.

SEE SECTIONS 8, 11 AND 12 FOR TOXICOLOGICAL INFORMATION.

### SECTION 3: Composition/Information on ingredients

MATERIAL	CAS#	EINECS#	WT %
n-Butyl Acetate	123-86-4	204-658-1	35-45
Xylenes	1330-20-7	215-535-7	15-25
Cellulose Acetate Butyrate	9004-36-8	-	5-15
Methyl Isobutyl Ketone	108-10-1	203-550-1	0-10
Ethylbenzene	100-41-4	202-849-4	0-10
Isopropanol	67-63-0	200-661-7	0-5
Polyethylene Powder	9002-88-4	-	0-1
Polyamine Amide Salt	Confidential	-	0-1

The specific chemical component identities and/or the exact component percentages of this material may be withheld as trade secrets. This information is made available to health professionals, employees, and designated representatives in accordance with the applicable provisions of 29 CFR 1910.1200 (I)(1).

TRACE COMPONENTS: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### SECTION 4: First aid measures

#### 4.1 Most Important Symptoms/Effects, Acute and Chronic

See Section 11 for Symptoms/Effects (acute and chronic)

#### 4.2 Eye Contact

For eyes, flush with plenty of water for 15 minutes and get medical attention.

#### 4.3 Skin Contact

In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap and water. Wash contaminated clothing before reuse.

#### 4.4 Inhalation

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

#### 4.5 Swallowing

Rinse mouth. Give a slurry of activated charcoal in water to drink. Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Rest. Do NOT give liquids to an unconscious or convulsing person.

### SECTION 5: Firefighting measures

#### 5.1 Fire and Explosion Preventive Measures

NO open flames, NO sparks, and NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

#### 5.2 Suitable (and Unsuitable) Extinguishing Media

Use dry powder, AFFF, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.

#### 5.3 Special Protective Equipment and Precautions for Fire Fighters

Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves and rubber boots).

#### 5.4 Specific Hazards of Chemical and Hazardous Combustion Products

HIGHLY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE

Isolate from oxidizers, heat, sparks, electric equipment and open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

### SECTION 6: Accidental release measures

#### 6.1 Spill and Leak Response and Environmental Precautions

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. No action shall be taken involving personal risk without suitable training. Keep unnecessary and unprotected personnel from entering spill area. Do not touch or walk through material. Avoid breathing vapor or mist. Provide adequate ventilation. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel. ELIMINATE all ignition sources (no smoking, flares, sparks, or flames in immediate area).

#### 6.2 Personal Precautions, Protective Equipment, Emergency Procedures

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves, they should be Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard-hat, and Self-Contained Breathing Apparatus specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat, and Self-Contained Breathing Apparatus or respirator.

Personal protective equipment are required wherever engineering controls are not adequate or conditions for potential exposure exist. Select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

#### 6.3 Environmental Precautions

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### 6.4 Methods and Material for Containment and Clean-Up

Absorb spilled liquid with polyps or other suitable absorbed materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. Dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

### 6.5 Notification Procedures

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. US regulations require reporting release of this material to the environment which exceed the applicable reportable quantity or oil spills which could reach any waterway including intermittent dry creeks. The National Response Center can be reached at (800) 424-8802.

## SECTION 7: Handling and storage

### 7.1 Precautions for Safe Handling

Isolate from oxidizers, heat, sparks, electric equipment and open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin and eyes. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron and footwear impervious to material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

### 7.2 Conditions for Safe Storage, Including any Incompatibilities

Keep in fireproof surroundings. Keep separated from strong oxidants, strong acids, strong bases. Keep cool. Do not store above 49 C / 120 F. Keep container tightly closed and upright when not in use to prevent leakage.

## SECTION 8: Exposure controls/personal protection

### 8.1 Exposure Limits

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
n-Butyl Acetate	123-86-4	204-658-1	150 ppm	150 ppm
Xylenes	1330-20-7	215-535-7	100 ppm	100 ppm A4
Cellulose Acetate Butyrate	9004-36-8	-	None Known	None Known
Methyl Isobutyl Ketone	108-10-1	203-550-1	100 ppm	20 ppm A3
Ethylbenzene	100-41-4	202-849-4	100 ppm	100 ppm A3
Isopropanol	67-63-0	200-661-7	400 ppm	200 ppm A4
Polyethylene Powder	9002-88-4	-	None Known	None Known
Polyamine Amide Salt	Confidential	-	None Known	None Known

MATERIAL	CAS#	EINECS#	CEILING	STEL (OSHA/ACGIH)	HAP
n-Butyl Acetate	123-86-4	204-658-1	None Known	200 ppm	No
Xylenes	1330-20-7	215-535-7	None Known	150 ppm	Yes
Methyl Isobutyl Ketone	108-10-1	203-550-1	None Known	75 ppm	Yes
Ethylbenzene	100-41-4	202-849-4	None Known	125 ppm	Yes
Isopropanol	67-63-0	200-661-7	None Known	400 ppm	No

In addition, using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%): Benzene, Toluene, Cumene

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### 8.2 Appropriate Engineering Controls

#### 8.2.1 RESPIRATORY EXPOSURE CONTROLS

Airborne concentrations should be kept to lowest levels possible. If vapor, dust or mist is generated and the occupational exposure limit of the product, or any component of the product, is exceeded, use appropriate NIOSH or MSHA approved air purifying or air-supplied respirator authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations, after determining the airborne concentration of the contaminant. Air supplied respirators should always be worn when airborne concentration of the contaminant or oxygen content is unknown. Maintain airborne contaminant concentrations below exposure limits. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For particulates, a particulate respirator (NIOSH Type N95 or better filters) may be worn. If oil particles (such as: lubricants, cutting fluids, glycerin, and so on) are present, use a NIOSH Type R or P filter. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

#### 8.2.2 EMERGENCY OR PLANNED ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS

Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxiliary positive pressure Self-Contained Breathing Apparatus.

#### 8.2.3 VENTILATION

LOCAL EXHAUST: Necessary

MECHANICAL (GENERAL): Necessary

SPECIAL: None

OTHER: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

### 8.3 Individual Protection Measures, such as Personal Protective Equipment

#### 8.3.1 EYE PROTECTION

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, chemical splash goggles should be worn, when a higher degree of protection is necessary, use splash goggles or safety glasses. Face-shields are recommended when the operation can generate splashes, sprays or mists.

#### 8.3.2 HAND PROTECTION

Use gloves chemically resistant to this material. Glove must be inspected prior to use. Preferred examples: Butyl rubber, Chlorinated Polyethylene, Polyethylene, Ethyl Vinyl Alcohol Laminate ("EVAL"), Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"), Neoprene, Nitrile/butadiene rubber ("nitrile") or ("NBR"), Polyvinyl chloride ("PVC") or "vinyl", Viton. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for protection time of the gloves cannot be accurately estimated. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good practices. Wash and dry hands.

#### 8.3.3 BODY PROTECTION

Use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

#### 8.3.4 WORK AND HYGIENIC PRACTICES

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using toilet facilities and at the end of the working period. Provide readily accessible eye wash stations and safety showers. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Appearance	: Liquid, Opaque, Off-White
Odor	: Ketone
Odor Threshold	: No data available
pH (Neutrality)	: No data available
Melting Point/Freezing Point	: No data available
Boiling Range (IBP, 50%, Dry Point)	: 82 111 141* C / 180 233 287°F (*=End Point)
Flash Point (Test Method)	: 13 C / 56 F (TCC) (Lowest Component)
Evaporation Rate (n-Butyl Acetate = 1)	: Not Applicable
Flammability Classification	: Class I B
Lower Flammable Limit in Air (% by vol)	: 1.5
Upper Flammable Limit in Air (% by vol)	: No data available
Vapor Pressure (mm of Hg) @20 C	: 11.3
Vapor Density (air=1)	: 3.6
Gravity @ 68/68 F / 20/20 C	:
Density	: 0.863
Specific Gravity (Water=1)	: 0.864
Pounds/Gallon	: 7.200
Water Solubility	: Moderate
Partition Coefficient (n-Octane/Water)	: No data available
Auto Ignition Temperature	: 398 C / 750 F
Decomposition Temperature	: No data available
Total VOC's (TVOC)*	: 88.0 Vol% / 757.7 g/L / 6.3 Lbs/Gal
Nonexempt VOC's (CVOC)*	: 88.0 Vol% / 757.7 g/L / 6.3 Lbs/Gal
Hazardous Air Pollutants (HAPS)	: 40.1 Wt% / 345.5 g/L / 2.8 Lbs/Gal
Nonexempt VOC Partial Pressure (mm of Hg @20 C)	: 0.0
Viscosity @ 20 C (ASTM D445)	: No data available

\* Using CARB (California Air Resources Board Rules).

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity and Chemical Stability

Stable under normal conditions, no hazardous reactions when kept from incompatible.

#### 10.2 Possibility of Hazardous Reactions and Conditions to Avoid

Isolate from oxidizers, heat, sparks, electric equipment and open flame.

#### 10.3 Incompatible Materials

The substance can presumably form explosive peroxides, under the influence of light and air. Check for peroxide prior to distillation, eliminate if found. Reacts violently with strong oxidants, strong reducing agents, strong acids, strong bases, causing fire and explosion hazard. Attacks many plastics, rubber, coatings.

#### 10.4 Hazardous Decomposition Products

Carbon Monoxide, Carbon Dioxide from burning.

#### 10.5 Hazardous Polymerization

Will not occur.

### SECTION 11: Toxicological information

#### 11.1 Acute Hazards

##### 11.1.1 EYE AND SKIN CONTACT

Primary irritation to skin, defatting, dermatitis. Absorption thru skin increases exposure. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

##### 11.1.2 INHALATION

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful. Breathing vapor can cause irritation. Acute overexposure can cause harm to affected organs by routes of entry. Use of alcoholic beverages enhances the harmful effect.

##### 11.1.3 SWALLOWING

ASPIRATION HAZARD! Harmful or fatal if swallowed. Do NOT induce vomiting. If spontaneous vomiting occurs, keep victim's head below the waist to prevent aspiration. Swallowing can cause abdominal irritation, nausea, vomiting and diarrhea. The symptoms of chemical pneumonitis may not show up for a few days.

#### 11.2 Subchronic Hazards/Conditions Aggravated

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing disorders of any target organs mentioned in this Document can be aggravated by over-exposure by routes of entry to components of this product. Persons with these disorders should avoid use of this product.

#### 11.3 Chronic Hazards

##### 11.3.1 CANCER, REPRODUCTIVE AND OTHER CHRONIC HAZARDS

Potential Cancer Hazard based on tests with laboratory animals using Methyl Isobutyl Ketone and Ethylbenzene. Overexposure may create cancer risk. Leukemia been reported in humans from Benzene. This product contains less than 31 ppm of Benzene. Not considered hazardous in such low concentrations. Absorption thru skin may be harmful. Studies with laboratory animals indicate this product can cause damage to fetus. Depending on degree of exposure, periodic medical examination is indicated. Some persons may be more sensitive to the substance's effect on blood cells.

##### 11.3.2 TARGET ORGANS

May cause damage to target organs, based on animal data.

##### 11.3.3 IRRITANCY

Irritating to contaminated tissue.

##### 11.3.4 SENSITIZATION

No component is known as a sensitizer.

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### 11.3.5 MUTAGENICITY

No known reports of mutagenic effects in humans.

### 11.3.6 EMBRYOTOXICITY

No known reports of embryotoxic effects in humans.

### 11.3.7 TERATOGENICITY

No known reports of teratogenic effects in humans.

### 11.3.8 REPRODUCTIVE TOXICITY

No known reports of reproductive effects in humans.

A MUTAGEN is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate across generational lines. An EMBRYOTOXIN is a chemical which causes damage to a developing embryo (such as: within the first 8 weeks of pregnancy in humans), but the damage does not propagate across generational lines. A TERATOGEN is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A REPRODUCTIVE TOXIN is any substance which interferes in any way with the reproductive process.

## 11.4 Mammalian Toxicity Information

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Methyl Isobutyl Ketone	108-10-1	-	LOWEST KNOWN LD50 (ORAL) 2080.0 mg/kg (Rats)
n-Butyl Acetate	123-86-4	204-658-1	LOWEST KNOWN LC50 (VAPORS) 2000 ppm (Rats)

## SECTION 12: Ecological information

### 12.1 ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION

### 12.2 Effect of Material on Plants and Animals

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

### 12.3 Effect of Material on Aquatic Life

The most sensitive known aquatic group to any component of this product is:

Chub 1000 ppm or mg/L (24 hour exposure).

Keep out of sewers and natural water supplies. The substance is toxic to aquatic organisms.

### 12.4 Mobility in Soil

Mobility of this material has not been determined.

### 12.5 Degradability

This product is partially biodegradable.

### 12.6 Accumulation

Bioaccumulation of this product has not been determined.



# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### SECTION 13: Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE USED CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY BURST AND CAUSE INJURY OR DEATH. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001

### SECTION 14: Transport information

IF > 401 LB / 182 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF XYLENE. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

MARINE POLLUTANT: NO

DOT/TDG SHIP NAME: UN1263, Paint Related Material (Contains: n-Butyl Acetate, Xylene), 3, PG-II

DRUM LABEL: (FLAMMABLE LIQUID)

IATA/ICAO: UN1263, Paint Related Material (Contains: n-Butyl Acetate, Xylene), 3, PG-II

IMO/IMDG: UN1263, Paint Related Material (Contains: n-Butyl Acetate, Xylene) 3, PG-II

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128



### SECTION 15: Regulatory information

#### 15.1 EPA Regulation

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG.SECTION)	RQ (LBS)
n-Butyl Acetate	123-86-4	204-658-1	35-45	(311, 312)	5000
*Xylenes	1330-20-7	215-535-7	15-25	(311, 312, 313, RCRA)	100
*Methyl Isobutyl Ketone	108-10-1	203-550-1	0-10	(311, 312, 313, RCRA)	5000
*Ethylbenzene	100-41-4	202-849-4	0-10	(311, 312, 313, RCRA)	1000

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State and local regulations may be more restrictive than federal regulations.

#### 15.2 State Regulations

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65):

This product contains the following chemicals known to the State of California to cause cancer: Methyl Isobutyl Ketone, Ethylbenzene

# On Track Refinish Basecoat Balancer (ONT.150B)

## Safety Data Sheet ONT.150B

### 15.3 International Regulations

The identified components of this product are listed on the chemical inventories of the following countries:

Australia (AICS)  
Canada (DSL or NDSL)  
China (IECSC)  
Europe (EINECS, ELINCS)  
Japan (METI/CSCL, MHLW/ISHL)  
South Korea (KECI)  
New Zealand (NZIoC)  
Philippines (PICCS)  
Switzerland (SWISS)  
Taiwan (NECSI)  
USA (TSCA)

### 15.4 CANADA: Workplace Hazardous Materials Information System (WHMIS)

B2: Flammable Liquid.

D2A: Contains a substance known to cause serious chronic toxicity or death: Ethylbenzene

D2B: Irritating to eyes/skin.

This product was classified using the hazard criteria of the Controlled Products Regulations (CPR). This Document contains all information required by the CPR.

## SECTION 16: Other information

### 16.1 Hazard Ratings

HEALTH (NFPA): 2, HEALTH (HMIS):2, FLAMMABILITY: 3, PHYSICAL HAZARD: 0

(Personal Protection Rating to be supplied by user based on use conditions.) This information is intended solely for the use of individuals trained in the NFPA and HMIS hazard rating systems.

### 16.2 Employee Training

See Section 2 (Hazards Identification). Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

### 16.3 SDS Date: 02/01/2015

## NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operations conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not release to its use in combination with any other material or process.

Unless updated, the Safety Data Sheet is valid until 02/01/2018.