



On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

Date of Preparation: 10/26/2016 Date of Revision: 03/29/2017 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	:	Black Low VOC Undercoating, Aerosol
Product Description	:	Rubberized Undercoating, Paintable, Black, Aerosol
General Use	:	Aerosol Coating, Automotive Use Only

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier

MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Classification of the Substance or Mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

2.2 Health Hazards

Eye Irritation, Category 2
Skin Irritation, Category 2
Target Organ Toxicity (Single Exposure), Category 3 (Narcotic Effects)
Target Organ Toxicity (Repeated Exposure), Category 2
Reproductive Toxicity, Category 2
Carcinogenicity, Category 2

2.3 Physical Hazards

Flammable Aerosols, Category 1
Gases Under Pressure
Simply Asphyxiants, Category 1

2.4 Label Elements

Hazardous components for labeling:

Acetone, Toluene and Carbon Black

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

2.5 Signal Word

DANGER

2.6 Hazard Statement(s)

H222: Extremely flammable aerosol.

H280: Contains gas under pressure; may explode if heated.

H319: Causes serious eye irritation.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to central nervous system through prolonged or repeated exposure.

H361: Suspected of damaging fertility or the unborn child.

H351: Suspected of causing cancer.

H600: May displace oxygen and cause rapid suffocation.

2.7 Precautionary Statement(s)

PREVENTION:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P264: Wash hands thoroughly after handling.

P260: Do not breathe mist, vapors or spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves and eye protection.

RESPONSE:

P308+P313: IF exposed or concerned: Get medical advice/attention.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P362: Take off contaminated clothing.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

STORAGE:

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

DISPOSAL:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

2.8 Hazards Not Otherwise Classified

No data available.

2.9 Emergency Overview

IMMEDIATE CONCERNS:

Flammable aerosol. Harmful if inhaled. Possible risk of harm to the unborn child. Suspected of causing cancer. Causes serious eye irritation. Irritating to skin. Vapors may cause drowsiness and dizziness. Vapor reduces oxygen availability for breathing.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

2.10 Comments

See sections 9 and 10 for more detailed information on physicochemical effects.
See section 11 for more detailed information on health effects.
See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial/professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

SECTION 3: Composition/Information on ingredients

CHEMICAL NAME	WT.%	CAS NUMBER
Acetone	40-45	67-64-1
Toluene	15-20	108-88-3
Propane	12-18	74-98-6
Isobutane	5-8	75-28-5
Carbon Black	0.5-1	1333-86-4

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Eye Contact

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

4.2 Skin Contact

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

4.3 Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

4.4 Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

4.5 Signs and Symptoms of Overexposure

EYE CONTACT: Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

SKIN CONTACT: Contact causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

4.6 Notes to Physician

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

4.7 Additional Information

No data available.

SECTION 5: Firefighting measures

5.1 Flammable Properties

Extremely flammable aerosol. Can readily explode for explosive mixtures at or above the flash point. Product can be ignited by static discharge.

5.2 Extinguishing Media

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

5.3 Hazardous Combustion Products

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.4 Fire Fighting Procedures

Containers can build up pressure if exposed to heat (fire).

5.5 Fire Fighting Equipment

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

5.6 Sensitivity to Static Discharge

Product is sensitive to static discharge.

5.7 Sensitivity to Mechanical Impact

Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120°F (49°C).

SECTION 6: Accidental release measures

6.1 Small Spill

Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

6.2 Environmental Precautions

WATER SPILL: Do not flush to sewer.

LAND SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

6.3 Special Protective Equipment

Clean up spills immediately, observing precautions in Protective Equipment section 8.

SECTION 7: Handling and storage

7.1 General Procedures

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

7.2 Handling

Contents under pressure. Do not expose to heat or store above 120°F (49°C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breathe vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

7.3 Storage

Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

SECTION 8: Exposure controls/personal protection

8.1 Exposure Guidelines

OSHA / WHMIS 2015 Hazardous Components

Chemical Name	Occupational Exposure Limits			
	Type		ppm	mg/m3
Acetone	OSHA PEL	TWA	1000	2400
	ACGIH TLV	TWA	500	1188
		STEL	750	1782
	NIOSH REL	TWA	250	590
Toluene	OSHA PEL	TWA	200	—
		STEL	300	—
	ACGIH TLV	TWA	20	75
	NIOSH REL	TWA	100	375
		STEL	150	560
Propane	OSHA PEL	TWA	1000	1800
	ACGIH TLV	TWA	1000	—
	NIOSH REL	TWA	1000	1800
Isobutane	ACGIH TLV	TWA	1000	—
	NIOSH REL	TWA	800	1900
Carbon Black	OSHA PEL	TWA	—	3.5
	ACGIH TLV	TWA	—[1]	3.5[1]
	NIOSH REL	TWA	—	3.5

Footnotes: 1. Inhalable particulate matter.

8.2 Engineering Controls

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

8.3 Personal Protective Equipment

EYES AND FACE: Wear safety glasses with side shields (or goggles).

SKIN CONTACT: Wear chemical resistant gloves.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

PROTECTIVE CLOTHING: Not applicable for aerosol containers.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

8.4 Work Hygienic Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid, without aerosol propellants
Odor	: Ketone
Odor Threshold	: No data available.
Appearance	: Aerosol
Color	: Black
pH	: Not Applicable
% Volatiles	: 80 to 85 % w/w
Flash Point and Method	: -18°C Setaflash Closed Cup, Acetone [lowest known value of aerosol concentrate]
Flammable Limits	: 1.0 to 12.8
Notes:	: Based on data for acetone
Autoignition Temperature	: 480°C
Notes	: Based on data for acetone [lowest known value of aerosol concentrate]
Vapor Pressure	: 50 - 60 psig at 20°C
Vapor Density	: > 1 (air = 1)
Boiling Point	: 56°C, Acetone [lowest known value of aerosol concentrate]
Freezing Point	: No data available
Melting Point	: No data available
Solubility in Water	: Partial
Evaporation Rate (n-Butyl Acetate = 1)	: > 1
Density	: 0.97 ± 0.02 g/ml at 20°C
Notes	: An estimate for the aerosol concentrate density
Viscosity	: > 100 cps
VOC Content	: ≤ 1.2 g O3 / g product [< 40% w/w]
Oxidizing Properties	: None

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

9.2 Flammability Statement

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability	Yes
Aerosol Flame Projection	> 15 cm but < 100 sm
Flashback	None

9.3 VOC Compliance Statement

Total Volatiles	<660 g/l 80-85% w/w
VOC Content	Product-Weighted Reactivity (PWR): <1.2 g O3/g Product < 40% w/w (<270 g/l)
VOC Regulation	USA National VOC Emission Standards for Aerosol Coatings - 40CFR PART 59 SUBPART E
Coating Category	Flat Coatings
The VOC Content meets the 1.20 PWR category limit for Flat Coatings. USA Compliant.	
VOC Regulation	California - Regulation for Reducing Emissions from Consumer Products - Title 17, California
Coating Category	Undercoating, Aerosol
The VOC Content meets the 40% w/w VOC limit for Aerosol Undercoatings. California compliant.	

SECTION 10: Stability and reactivity

10.1 Reactive Hazard

No

10.2 Hazardous Polymerization

Not expected to occur.

10.3 Stability

Stable.

10.4 Conditions to Avoid

Keep away from flames and any object that sparks. Container may explode if heated.

10.5 Possibility of Hazardous Reactions

No data available.

10.6 Hazardous Decomposition Products

Carbon Monoxide and other toxic vapors.

10.7 Incompatible Materials

Oxidizing materials.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

SECTION 11: Toxicological information

11.1 Acute Toxicity

CHEMICAL NAME	ORAL LD50 mg/kg (rat)	DERMAL LD50 mg/kg (rabbit)	INHALATION LC50 mg/l
Acetone	8400 5250 (mouse) 5300 (rabbit)	> 15,700	50.1 (rat;8h) 44.0 (mouse;4h)
Toluene	7000 6400 5500	12,270	49.0 (rat;4h) 30.0 (mouse;2h) 19.9 (mouse;7h)
Propane	Not Applicable	Not Applicable	> 20,000 ppm (rat;4h)
Isobutane	Not Applicable	Not Applicable	142.5 ppm (rat;4h)
Carbon Black	> 15,400	> 3000	Not Applicable

11.1.1 Acute Toxicity - Dermal LD50:

Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

11.1.2 Acute Toxicity - Oral LD50:

Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

11.1.3 Acute Toxicity - Inhalation LC50:

Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapors) and >5 mg/l/4h (mists).

11.1.4 Notes:

20% of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

11.1.5 Skin Irritation/Corrosion:

Contains: Toluene. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

11.1.6 Eye Irritation/Serious Eye Damage:

Contains: Acetone. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

11.1.7 Respiratory/Skin Sensitizer:

Based on available data, the classification criteria for skin/respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a skin/respiratory sensitizer, sub-category 1B).

11.1.8 Germ Cell Mutagenicity:

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

11.2 Carcinogenicity

Chemical Name	NTP Status	IARC Status	OSHA Status	Other
Acetone	—	—	—	A4 (ACGIH)
Toluene	—	3	—	A4 (ACGIH)
Propane	—	—	—	—
Isobutane	—	—	—	—
Carbon Black	—	2B	—	A3 (ACGIH)

NOTES: Contains: Carbon Black. Carbon black is listed as Group 2B (possibly carcinogenic to humans). The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as a Carcinogen, category 2).

11.3 Reproductive Toxicity

The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as Reproductive Toxicity, category 2). May cause adverse reproductive effects. Possible risk of harm to the unborn child (Toluene).

11.4 Specific Target Organ Toxicity - Single Exposure

Contains: Toluene and Solvent naphtha light aliphatic. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ($\geq 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

11.5 Specific Target Organ Toxicity - Repeated Exposure

The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Toluene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

11.6 Aspiration Hazard

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ($< 10\%$ ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm²/s at 40°C).

SECTION 12: Ecological information

12.1 Environmental Data

No data available.

12.2 Ecotoxicological Information

No data available.

12.3 Bioaccumulation/Accumulation

No data available.

12.4 Distribution

No data available.

12.5 Aquatic Toxicity (Acute)

No data available.

12.6 Chemical Fate Information

No data available.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

SECTION 13: Disposal considerations

13.1 Disposal Method

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

13.2 Product Disposal

When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

SECTION 14: Transport information

14.1 DOT (Department of Transportation)

Proper Shipping Name	Aerosols, Flammable
Primary Hazard Class/Division	2.1
UN/NA Number	1950
Packing Group	N/AP
Other Shipping Information	With an inner packaging <1.0 L, this product may be shipped as a Limited Quantity as per DOT 173.306.

14.2 Air (ICAO/IATA)

Shipping Name	Aerosols, Flammable
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
Subsidiary Risk	None
Label	Flammable Gas

14.3 Vessel (IMO/IMDG)

Shipping Name	Aerosols
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
Marine Pollutant	None
Label	None

Note: With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

14.4 Canadian Transportation of Dangerous Goods Regulations

Shipping Name	Aerosols, Flammable
UN/NA Number	1950
Primary Hazard Class/Division	2.1
Packing Group	N/AP
TDG Note	With an inner packaging <1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

SECTION 15: Regulatory information

15.1 United States

15.1.1 SARA Section 311/312 Hazard Categories

311/312 HEALTH HAZARDS: Carcinogenicity, Eye Irritation, Reproductive Toxicity, Simply Asphyxiant, Skin irritation, Target Organ Toxicity (Repeated exposure), Target Organ Toxicity (Single exposure)

311/312 Physical Hazards: Flammable Aerosols, Gases Under Pressure

Fire Hazard: Yes

Sudden Release of Pressure: Yes

Reactive Hazard: No

Product Acute Toxicity: Yes

Product Chronic Toxicity: Yes

15.1.2 EPCRA Section 313 Toxic Chemicals

CHEMICAL NAME	WT.%	CAS number
Toluene	15-20	108-88-3

15.1.3 EPCRA Section 302 Extremely Hazardous Substances

EPCRA STATUS: This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

15.1.4 CERCLA Hazardous Substances and Reportable Quantities (RQ)

Chemical Name	Wt. %	RQ
Acetone	40-45	5,000
Toluene	15-20	1,000

15.1.5 TSCA (The Toxic Substances Control Act)

TSCA Status: All components are included or are otherwise exempt from inclusion on this inventory.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

15.1.6 CAA 112 (b) - Hazardous Air Pollutants

Chemical Name	WT.%	CAS Number
Toluene	15-20	108-88-3

15.1.7 CAA 112 (r) - List of Substances for Accidental Release Prevention

NAME	CAS NO.	THRESHOLD QTY (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

15.1.8 California Proposition 65

CHEMICAL NAME	WT.%	LISTED
Toluene	15-20	- Developmental Toxicity - Female Reproductive
Carbon Black	0.5-1	Cancer

15.1.9 OSHA Hazard Communication Standard (29 CFR 1910.1200)

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29 CFR 1900.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

15.2 Canada

15.2.1 WHMIS Hazard Symbol and Classification

See Section 2 for details.

15.2.2 WHMIS Regulatory Status

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

15.2.3 WHMIS Classification

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

15.2.4 CEPA - National Pollutant Release Inventory (NPRI)

Name	CAS No.	NPRI Part No.
Toluene	108-88-3	1A, 5 (VOC)
Propane	74-98-6	5 (VOC)
Butane (all isomers)	75-25-5	5 (VOC)

15.2.5 Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL)

All components are included or are otherwise exempt from inclusion on this inventory.

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

15.3 Comments

VOC Content - See section 9.

SECTION 16: Other information

16.1 Date Revised

03/29/2017

16.2 HMIS Rating

HEALTH - *2

FLAMMABILITY - 3

PHYSICAL HAZARD - 0

PERSONAL PROTECTION - B

16.3 NFPA Codes

NFPA 30 / 30B Storage Classification: Level 2 Aerosol

Manufacturer Supplemental Notes: None

Data Sources: Not Available.

ADDITIONAL SDS INFORMATION:

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

GENERAL STATEMENTS: None

On Track Refinish PBR (ONT.PBR)

Safety Data Sheet ONT.PBR

COMMENTS: None

MANUFACTURER DISCLAIMER:

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.