



# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

Date of issue: 11/03/2016 Date of Revision: 06/28/2018 Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Description : Paint Stripper, Aerosol 510 g / 1 lb 2 oz  
General Use : Paint Stripper  
Chemical Family : Solvent-based

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Supplier**  
MCGEHEE & MCGEHEE ENTERPRISES INC  
120 SOUTH BOGGESS AVENUE  
- USA  
T (270) 338-4600 - F (270) 338-4602

#### 1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the Substance or Mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulation (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

#### 2.2 Health Hazards

Acute Toxicity (Oral), Category 4  
Skin Irritation, Category 2  
Eye Irritation, Category 2  
Target Organ Toxicity (Single Exposure), Category 2  
Target Organ Toxicity (Single Exposure), Category 3 (Respiratory Tract Irritation and Narcotic Effects)  
Target Organ Toxicity (Repeated Exposure), Category 2  
Carcinogenicity, Category 2  
Reproductive Toxicity, Category 2

#### 2.3 Physical Hazards

Flammable Aerosols, Category 1  
Gases Under Pressure  
Simple Asphyxiants, Category 1

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 2.4 Label Elements

Hazardous components for labelling:

Methylene chloride, Toluene and Methanol



### 2.5 Signal Word

DANGER

### 2.6 Hazard Statement(s)

H222: Extremely flammable aerosol.

H280: Contains gas under pressure; may explode if heated.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H371: May cause blindness if swallowed.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to central nervous system, kidneys and liver through prolonged or repeated exposure.

H351: Suspected of causing cancer.

H361: Suspected of damaging fertility or the unborn child.

H600: May displace oxygen and cause rapid suffocation.

### 2.7 Precautionary Statement(s)

PREVENTION:

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe mist, vapors or spray.

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves, protective clothing and eye protection.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

RESPONSE:

P308+P313: IF EXPOSED OR CONCERNED: Get medical advice/attention.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water.

P332+P313: If skin irritation occurs; Get medical advice/attention.

P362+P364: Take off contaminated clothing and wash it before reuse.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P330: Rinse mouth.

STORAGE:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P405: Store locked up.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.

### DISPOSAL:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

### 2.8 Hazards Not Otherwise Classified

No data available.

### 2.9 Emergency Overview

**IMMEDIATE CONCERNS:** Extremely flammable aerosol. Irritating to eyes, skin and respiratory system. Vapors may cause drowsiness and dizziness. May cause blindness if swallowed. May be harmful if swallowed. Prolonged or repeated exposure may cause central nervous system, kidney and liver damage. May cause cancer. Possible risk of harm to the unborn child. Vapor reduces oxygen availability for breathing.

### 2.10 Comments

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.

See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See section 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial/professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

## SECTION 3: Composition/Information on ingredients

CHEMICAL NAME	WT.%	CAS NUMBER
Methylene Chloride	70-74	75-09-2
Isobutane	10-14	75-28-5
Toluene	4-6	108-88-3
Methanol	4-6	67-56-1
Propane	2-4	74-98-6

COMMENTS: There are not additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

## SECTION 4: First aid measures

### 4.1 Eye Contact

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

### 4.2 Skin Contact

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

### 4.3 Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

### 4.4 Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 4.5 Signs and Symptoms of Overexposure

#### EYE CONTACT:

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and or a feeling like that of fine dust in the eyes.

SKIN CONTACT: Causes severe skin irritation. May be absorbed through the skin in harmful amounts. Vapor inhalation and/or skin absorption can cause central nervous system effects and blindness.

INGESTION: May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea. Poison, May be fatal or cause blindness if swallowed.

INHALATION: High vapor or spray mist concentrations may be harmful if inhaled. Prolonged or excessive inhalation may cause respiratory tract irritation. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness). Prolonged or repeated inhalation may cause lung damage and/or central nervous system disturbances. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

Notes to Physician: Treatment of overexposure should be directed at the control of symptoms and the clinical conditions of the patient.

Additional Information: No data available.

## SECTION 5: Firefighting measures

### 5.1 Flammable Properties

Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point.

### 5.2 Extinguishing Media

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

### 5.3 Hazardous Combustion Products

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

### 5.4 Fire Fighting Procedures

Containers can build up pressure if exposed to heat (fire).

### 5.5 Fire Fighting Equipment

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

### 5.6 Sensitivity to Static Discharge

Product is sensitive to static discharge.

### 5.7 Sensitivity to Mechanical Impact

Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120°F (49°C).

## SECTION 6: Accidental release measures

### 6.1 Small Spill

Eliminate all ignition sources. Ensure adequate ventilation. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

### 6.2 Environmental Precautions

WATER SPILL: Do not flush to sewer.

LAND SPILL: Avoid runoff into storm sewers and ditches which lead to waterways.

### 6.3 Special Protective Equipment

Clean up spills immediately, observing precautions in Protective Equipment section 8.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### SECTION 7: Handling and storage

#### 7.1 General Procedures

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids. Ensure thorough ventilation of stores and work areas.

#### 7.2 Handling

Contents under pressure. Do not expose to heat or store above 120°F (49°C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breathe vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

#### 7.3 Storage

Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

# On Track Coating Stripper (ONT.A-0110)

Safety Data Sheet ONT.A-0110

## SECTION 8: Exposure controls/personal protection

### 8.1 Exposure Guidelines

#### OSHA / WHMIS 2015 HAZARDOUS COMPONENTS

CHEMICAL NAME	OCCUPATIONAL EXPOSURE LIMITS			
	TYPE		ppm	mg/m3
Methylene Chloride	OSHA PEL	TWA	25	—
		STEL	125	—
	ACGIH TLV	TWA	50	173
Isobutane	ACGIH TLV	TWA	1000	—
	NIOSH REL	TWA	800	1900
Toluene	OSHA PEL	TWA	200	—
		STEL	300	—
	ACGIH TLV	TWA	20	75
	NIOSH REL	TWA	100	375
		STEL	150	560
Methanol	OSHA PEL	TWA	200	260
	ACGIH TLV	TWA	200	262
		STEL	250	328
	NIOSH REL	TWA	200	260
		STEL	250	325
Propane	OSHA PEL	TWA	1000	1800
	ACGIH TLV	TWA	1000	—
	NIOSH REL	TWA	1000	1800

### 8.2 Engineering Controls

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 8.3 Personal Protective Equipment

**EYES AND FACE:** Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

**SKIN CONTACT:** Wear chemical resistant gloves.

**RESPIRATORY:** If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

**PROTECTIVE CLOTHING:** wear protective clothing as necessary to prevent contact.

### 8.4 Work Hygienic Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/ was thoroughly before reuse.

# On Track Coating Stripper (ONT.A-0110)

Safety Data Sheet ONT.A-0110

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid, without aerosol propellants
Odor	: Sweet, chloroform-like
Odor Threshold	: No data available
Appearance	: Aerosol
Color	: Opaque, Translucent
pH	: No data available
% Volatiles	: 97 to 98 % w/w
Flash Point and Method	: 4°C Setaflash Closed Cup, Toluene [lowest known value of aerosol concentrate]
Flammable	: 1.0 to 10.8
Autoignition Temperature	: No data available.
Vapor Pressure	: 25 - 40 psi at 25°C
Vapor Density	: > 1 (air=1)
Boiling Point	: 40°C, Methylene Chloride [lowest known value of aerosol concentrate]
Freezing Point	: No data available
Melting Point	: No data available
Solubility in Water	: Partial
Evaporation Rate (n-butyl acetate=1)	: > 1
Density	: No data available
Viscosity	: > 100 cps at 25 °C
VOC Content	: 24 - 26% w/w
Oxidizing Properties	: None



# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 9.2. Flammability Statement

THE FLAMMABILITY OF AN AEROSOL IS DETERMINED BY ITS FLAME EXTENSION AND/OR FLASHBACK.

Flammability	:	Yes
Aerosol Flame Projection	:	> 15 cm but < 100 cm
Flashback	:	None
Calculated Aerosol Chemical Heat of Combustion, kJ/g	:	< 15

### 9.3. VOC Compliance Statement

Total Volatiles	:	97 to 98% w/w
VOC Content	:	24 to 26% w/w
VOC Regulation	:	CARB-California, OTC state Consumer Product Regulations
Product Category	:	Paint Remover or Stripper

The product VOC content meets the current 50% w/w limit under the CARB.

Consumer Product Regulations for Paint Remover or Stripper

50 State compliant.

## SECTION 10: Stability and reactivity

### 10.1. Reactive Hazard

No

### 10.2. Hazardous Polymerization

Not expected to occur.

### 10.3. Stability

Stable under normal conditions of use and storage.

### 10.4. Conditions to Avoid

Keep away from flames and any object that sparks. Container may explode if heated.

### 10.5. Possibility of Hazardous Reactions

Strong exothermic reaction with strong oxidants and strong acids.

### 10.6. Hazardous Decomposition Products

By fire and high heat: Carbon monoxide, Carbon dioxide and other undetermined compounds.

### 10.7. Incompatible Materials

Strong oxidizing agents and strong bases.

# On Track Coating Stripper (ONT.A-0110)

Safety Data Sheet ONT.A-0110

## SECTION 11: Toxicological information

### 11.1 Acute Toxicity

CHEMICAL NAME	ORAL LD50 mg/kg (rat)	DERMAL LD50 mg/kg (rabbit)	INHALATION LC50 mg/l
Methylene Chloride	1600 (rat) 3000 (rat)	> 2000 (rat)	52.0 (rat;6h) 79.0 (rat;2h) 76.0 (rat;4h) 56.2 (mouse;7h) 49.1 (mouse;6h) 51.5 (mouse;2h)
Isobutane	Not Applicable	Not Applicable	142.5 ppm (rat;4h)
Toluene	7000 6400 5500	12,270	49.0 (rat;4h) 30.0 (mouse;2h) 19.9 (mouse;7h)
Methanol	6200 (rat) 5630 (rat) 7300 (mouse)	15,800	83.9 (rat;4h)
Propane	Not Applicable	Not Applicable	> 20,000 ppm (rat;4h)

#### ACUTE TOXICITY - DERMAL LD50:

Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg.

#### ACUTE TOXICITY - ORAL LD50:

Contains: Methylene chloride. Based on available ingredient data, the mixture is classified as: Acute Oral Toxicity, category 4. The calculated ATE is > 300 and ≤2000 mg/kg. May be harmful if swallowed.

#### ACUTE TOXICITY - INHALATION LC50:

Based on available ingredient data, the classification criteria for Acute Toxicity- inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapors) and > 5 mg/l/4h (mists). High vapor concentrations may be harmful if inhaled. Excessive vapor concentrations are attainable. Saturated vapors can be encountered in confined spaces and/or under conditions of poor ventilation.

#### NOTES:

< 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity. No additional toxicology information is available for this product itself. (See Component Toxicity Information).

### 11.2 Skin Irritation/Corrosion

Contains: Methylene chloride and Toluene. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

### 11.3 Eye Irritation/Serious Eye Damage

Contains: Methylene chloride and methanol. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

### 11.4 Respiratory/Skin Sensitizer

Based on available data, the classification criteria for respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a respiratory sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a respiratory sensitizer, sub-category 1B).

Based on available data, the classification criteria for skin sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a skin sensitizer, sub-category 1B).

### 11.5 Germ Cell Mutagenicity

Based on available data, the classification criteria for Germ cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 11.6 Carcinogenicity

CHEMICAL NAME	NTP STATUS	IARC STATUS	OSHA STATUS	OTHER
Methylene Chloride	P	2B	X	A3 (ACGIH)
Isobutane	—	—	—	—
Toluene	—	3	—	A4 (ACGIH)
Methanol	—	—	—	—
Propane	—	—	—	—

NOTES: Contains: Methylene chloride. Methylene chloride is listed as Group 2B (possibly carcinogenic to humans). The mixture is classified as: Carcinogenicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as a carcinogen, category 2).

### 11.7 Reproductive Toxicity

Contains: Toluene. The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ( $\geq 0.1\%$  ingredients classified as Reproductive Toxicity, category 2). May cause adverse reproductive effects. Possible risk of harm to the unborn child (Toluene).

### 11.8 Specific Target Organ Toxicity - Single Exposure

Contains: Methanol. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ( $\geq 1.0\%$  ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 2). May cause damage to eyes and optic nerve.

Contains: Methylene chloride and Toluene. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ( $\geq 20\%$  summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3 [Narcotic Effects]). Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

Contains: Methylene chloride. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ( $\geq 20\%$  summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3 [Respiratory Tract Irritation]). Prolonged or excessive inhalation may cause respiratory tract irritation. Vapor/mists at concentrations above the exposure limits can irritate (burning sensation) the mucous membranes in the respiratory tract.

### 11.9 Specific Target Organ Toxicity - Repeated Exposure

Contains: Methylene chloride and Toluene. The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ( $\geq 1.0\%$  ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). May cause damage to central nervous system, kidneys and liver through prolonged or repeated exposure. Chronic exposure to organic solvents such as Toluene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

### 11.10 Aspiration Hazard

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ( $< 10\%$  ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity  $> 20.5$  mm<sup>2</sup>/s at 40°C).

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### SECTION 12: Ecological information

#### 12.1 Environmental Data

No data available.

#### 12.2 Ecotoxicological Information

No data available.

#### 12.3 Bioaccumulation/Accumulation

No data available.

#### 12.4 Distribution

No data available.

#### 12.5 Aquatic Toxicity (Acute)

No data available.

#### 12.6 Chemical Fate Information

No data available.

### SECTION 13: Disposal considerations

#### 13.1 Disposal Method

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

#### 13.2 Product Disposal

When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

### SECTION 14: Transport information

#### 14.1 DOT (Department of Transportation)

Proper Shipping Name	:	AEROSOLS
Primary Hazard Class/Division	:	2.1
UN/NA Number	:	1950
Packing Group	:	N/AP
Label	:	Class 2.1, Flammable Gases
Other Shipping Information	:	With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity as per DOT 173.306.

#### 14.2 Vessel (IMO/IMDG)

Shipping Name	:	AEROSOLS
UN/NA Number	:	1950
Primary Hazard Class/Division	:	2.1
Packing Group	:	N/AP
Marine Pollutant	:	None
Label	:	Class 2.1, Flammable Gases
Note	:	With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

### 14.3 Canadian Transportation of Dangerous Goods Regulations

Shipping Name	:	AEROSOLS
UN/NA Number	:	1950
Primary Hazard Class/Division	:	2.1
Packing Group	:	N/AP
Label	:	Class 2.1, Flammable Gases

### 14.4 TDG Note

For products with an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

## SECTION 15: Regulatory information

### 15.1 United States

#### SARA Section 311/312 Hazard Categories

311/312 Health Hazards: Acute Toxicity (Oral), Carcinogenicity, Eye Irritation, Narcotic Effects, Reproductive Toxicity, Respiratory Tract Irritation, Simple Asphyxiant, Skin Irritation, Target Organ Toxicity (Repeated exposure), Target Organ Toxicity (Single exposure).

311/312 Physical Hazards: Flammable Aerosols, Gases Under Pressure

#### EPCRA Section 313 Toxic Chemicals

CHEMICAL NAME	WT.%	CAS NUMBER
Methylene Chloride	70-74	75-09-2
Toluene	4-6	108-88-3
Methanol	4-6	67-56-1

#### EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status: This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

#### CERCLA Hazardous Substances and Reportable Quantities (RQ)

CHEMICAL NAME	WT.%	RQ
Methylene Chloride	70-74	1,000
Toluene	4-6	1,000
Methanol	4-6	5,000

#### TSCA (The Toxic Substances Control Act)

TSCA Status: All components are included or are otherwise exempt from inclusion on this inventory.

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

CHEMICAL NAME	WT.%	CAS NUMBER
Methylene Chloride	70-74	75-09-2
Toluene	4-6	108-88-3
Methanol	4-6	67-56-1

CAA 112(r) - List of Substances for Accidental Release Prevention

This product contains the following chemicals subject to CAA 112(r).

NAME	CAS NO.	THRESHOLD QTY (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

CALIFORNIA PROPOSITION 65

CHEMICAL NAME	WT.%	LISTED
Methylene Chloride	70-74	Cancer
Toluene	4-6	- Developmental Toxicity - Female Reproductive
Methanol	4-6	Developmental Toxicity

OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200):

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

### 15.2 Canada

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

NAME	CAS NO.	NPRI PART NO.
Methylene Chloride	75-09-2	1A
Toluene	108-88-3	1A, 5 (VOC)
Methanol	67-56-1	5 (VOC)
Propane	74-98-6	5 (VOC)
Butane (all isomers)	75-28-5	5 (VOC)

DOMESTIC SUBSTANCES LIST (DSL) / NON-DOMESTIC SUBSTANCES LIST (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

COMMENTS: VOC Content — See Section 9.

### SECTION 16: Other information

Date Revised: 06/28/2018

HMIS RATING:


HEALTH: \*2

FLAMMABILITY: 2

PHYSICAL HAZARD: 0

PERSONAL PROTECTION: G

NFPA CODES:



NFPA 30 / 30B Storage Classification: Level 1 Aerosol

Manufacturer Supplemental Notes: None

Data Sources: Not Available

Additional SDS Information:

# On Track Coating Stripper (ONT.A-0110)

## Safety Data Sheet ONT.A-0110

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Container Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

GENERAL STATEMENTS: None

COMMENTS: None

MANUFACTURER DISCLAIMER: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.