



Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

Date of issue: 06/02/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identifier : Water Based Pre Clean
Recommended Use : Cleaner
Recommended Restrictions : None Known.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier
MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 Physical Hazards

Flammable Liquids - Category 2

2.2 Health Hazards

Serious eye damage/eye irritation - Category 2A

2.3 Environmental Hazards

Not classified.

2.4 OSHA Defined Hazards

Not classified.

2.5 Label Elements



2.6 Signal Word

DANGER

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

2.7 Hazard Statement

Highly flammable liquid and vapor. Causes serious eye irritation.

2.8 Precautionary Statement

2.8.1 PREVENTION

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.

2.8.2 RESPONSE

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

2.8.3 STORAGE

Store in a well-ventilated place. Keep cool.

2.8.4 DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

2.9 Hazard(s) Not Otherwise Classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

2.10 Supplemental Information

None.

SECTION 3: Composition/Information on ingredients

3.1 Mixtures

CHEMICAL NAME	COMMON NAME AND SYNONYMS	CAS NUMBER	%
Acetone		67-64-1	5 - < 15
Butyl Cellosive/Glycol Ether EB		111-76-2	0 < 5
Methanol		67-56-1	0 < 5
Propylene Glycol		57-55-6	0 < 5
Other components below reportable levels			80 - < 90

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1 Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

4.2 Skin Contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

4.3 Eye Contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

4.4 Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.5 Most Important Symptoms/Effects, Acute and Delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

4.6 Indication of Immediate Medical Attention and Special Treatment Needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

4.7 General Information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

SECTION 5: Firefighting measures

5.1 Suitable Extinguishing Media

Alcohol resistant foam. Water fog. Carbon dioxide (CO₂). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

5.2 Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

5.3 Specific Hazards Arising from the Chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

5.4 Special Protective Equipment and Precautions for Firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

5.5 Fire Fighting Equipment/Instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

5.6 Specific Methods

Use standard firefighting procedures and consider the hazards of other involved materials.

5.7 General Fire Hazards

Highly flammable liquid and vapor.

SECTION 6: Accidental release measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

6.2 Methods and Materials for Containment and Cleaning Up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Keep combustibles (wood, paper, oil, etc.) away from spilled material.

LARGE SPILLS: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

SMALL SPILLS: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see Section 13 of the SDS.

6.3 Environmental Precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

SECTION 7: Handling and storage

7.1 Precautions for Safe Handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

7.2 Conditions for Safe Storage, including any Incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Kepe in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

SECTION 8: Exposure controls/personal protection

8.1 Occupational Exposure Limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m ³ 1000 ppm
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	PEL	240 mg/m ³ 50 ppm
Methanol (CAS 67-56-1)	PEL	260 mg/m ³ 200 ppm

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	TWA	20 ppm
Methanol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m ³
		250 ppm
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	TWA	24 mg/m ³
		5 ppm
Methanol (CAS 67-56-1)	STEL	325 mg/m ³
	TWA	250 ppm
		260 mg/m ³
		200 ppm

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
Propylene Glycol (CAS 57-55-6)	TWA	10 mg/m ³	Aerosol.

8.2 Biological Limit Values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*
Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	200 mg/g	Buoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Methanol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*

* - For sampling details, please see the source document.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

8.3 Exposure Guidelines

8.3.1 US - California OELs: Skin Designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

8.3.2 US - Minnesota Haz Subs: Skin Designation Applies

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Skin designation applies.
Methanol (CAS 67-56-1)	Skin designation applies.

8.3.3 US - Tennessee OELs: Skin Designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

8.3.4 US ACGIH Threshold Limit Values: Skin Designation

Methanol (CAS 67-56-1)	Can be absorbed through the skin.
------------------------	-----------------------------------

8.3.5 US NIOSH Pocket Guide to Chemical Hazards: Skin Designation

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Can be absorbed through the skin.
Methanol (CAS 67-56-1)	Can be absorbed through the skin.

8.3.6 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)	Can be absorbed through the skin.
---	-----------------------------------

8.4 Appropriate Engineering Controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

8.5 Individual Protection Measures, such as Personal Protective Equipment

8.5.1 Eye/Face Protection

Wear safety glasses with side shields (or goggles).

8.5.2 Skin Protection

HAND PROTECTION: Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

OTHER: Wear suitable protective clothing.

8.5.3 Respiratory Protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

8.5.7 Thermal Hazards

Wear appropriate thermal protective clothing, when necessary.

8.6 General Hygiene Considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	:	Liquid.
Form	:	Liquid.
Color	:	Colorless
Odor	:	Soapy
Odor Threshold	:	Not available
pH	:	Not available
Melting Point/Freezing Point	:	-138.46°F (-94.7°C) estimated
Initial Boiling Point and Boiling Range	:	132.89 °F (56.05°C) estimated
Flash Point	:	-4.0 °F (-20.0°C) estimated
Evaporation Rate	:	Not available
Flammability (solid, gas)	:	Not applicable.
Upper/lower Flammability or Explosive Limits		
Flammability Limit - Lower (%)	:	2.6% estimated
Flammability Limit - Upper (%)	:	12.8% estimated
Explosive Limit - Lower (%)	:	Not available.
Explosive Limit - Upper (%)	:	Not available.
Vapor Pressure	:	31.13 hPa estimated
Vapor Density	:	Not available.
Relative Density	:	Not available.
Solubility (water)	:	Not available.
Partition Coefficient (n-Octanol/Water)	:	Not available.
Auto-Ignition Temperature	:	869°F (465°C) estimated
Decomposition Temperature	:	Not available.
Viscosity	:	Not available.
Density	:	0.80 g/cm ³ estimated
Flammability Class	:	Flammable IB estimated
Percent Volatile	:	99.86 v/v % By Volume 99.86 w/w % By Weight
Specific Gravity	:	0.8 estimated
VOC (Weight %)	:	0.04 lb/gal (Actual VOC - With Water Less Exempts) 4.88 g/L (Actual VOC - With Water With Exempts) 5.97 lb/gal (Regulatory VOC - Less Water Less Exempts) 714.88 g/L (Regulatory VOC - Less Water Less Exempts)

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

SECTION 10: Stability and reactivity

10.1 Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2 Chemical Stability

Material is stable under normal conditions.

10.3 Possibility of Hazardous Reactions

Hazardous polymerization does not occur.

10.4 Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5 Incompatible Materials

Acids.

10.6 Hazardous Decomposition Products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on Likely Routes of Exposure

11.1.1 Inhalation

Prolonged inhalation may be harmful.

11.1.2 Skin Contact

No adverse effects due to skin contact are expected.

11.1.3 Eye Contact

Causes serious eye irritation.

11.1.4 Ingestion

Expected to be low ingestion hazard.

11.2 Symptoms Related to the Physical, Chemical and Toxicological Characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

11.3 Information on Toxicological Effects

11.3.1 Acute Toxicity

COMPONENTS	SPECIES	TEST RESULTS
ACETONE CAS # 67-64-1		
Acute		
Dermal LD50	Rabbit	20000 mg/kg 20 ml/kg
Inhalation LC50	Rat	76 mg/l, 4 Hours 50.1 mg/l, 8 Hours
Oral LD50	Mouse	3000 mg/kg
	Rabbit	5340 mg/kg
	Rat	5800 mg/kg
Butyl Cellosolve/Glycol Ether EB CAS # 111-76-2		
Acute		
Dermal LD50	Rabbit	400 mg/kg
Inhalation LC50	Mouse	700 ppm, 7 hours
	Rat	450 ppm, 4 hours
Oral LD50	Guinea Pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
Methanol CAS # 67-56-1		
Acute		
Dermal LD50	Rabbit	15800 mg/kg
Inhalation LC50	Cat	85.41 m/l, 4.5 hours 43.68 mg/l, 6 hours
	Rat	64000 ppm, 4 hours 87.5 mg/l, 6 hours
Oral LD50	Dog	8000 mg/kg
	Monkey	2 g/kg
	Mouse	7300 mg/kg
	Rabbit	14.4 g/kg
	Rat	5628 mg/kg

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

COMPONENTS	SPECIES	TEST RESULTS
	Propylene Glycol I CAS # 57-55-6 Acute	
Oral LD50	Dog	19 g/kg
	Guinea Pig	18.4 g/kg
	Mouse	23.9 g/kg
	Rabbit	18 g/kg
	Rat	30 g/kg

*Estimates for product may be based on additional component data not shown.

11.4 Skin Corrosion/Irritation

Prolonged skin contact may cause temporary irritation.

11.5 Serious Eye Damage/Eye Irritation

Causes serious eye irritation.

11.6 Respiratory or Skin Sensitization

RESPIRATORY SENSITIZATION:

Not a respiratory sensitizer.

SKIN SENSITIZATION:

This product is not expected to cause skin sensitization.

11.7 Germ Cell Mutagenicity

No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

11.8 Carcinogenicity

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

11.8.1 IARC Monographs. Overall Evaluation of Carcinogenicity

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) — 3 Not classifiable as to carcinogenicity to humans.

11.8.2 OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

11.9 Reproductive Toxicity

This product is not expected to cause reproductive or developmental effects.

11.10 Specific Target Organ Toxicity - Single Exposure

Not classified.

11.11 Specific Target Organ Toxicity - Repeated Exposure

Not classified.

11.12 Aspiration Hazard

Not an aspiration hazard.

11.13 Chronic Effects

Prolonged inhalation may be harmful.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

SECTION 12: Ecological information

12.1 Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

COMPONENTS	SPECIES	TEST RESULTS
Acetone CAS # 67-64-1 Aquatic		
Crustacea EC50	Water flea (Daphnia magna)	10294-17704 mg/l, 48 hours
Fish LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740-6330 mg/l, 96 hours
Butyl Cellosolve/Glycol Ether EB CAS # 111-76-2 Aquatic		
Fish LC50	Inland Silverside (Menidia beryllina)	1250 mg/l, 96 hours
Methanol CAS # 67-56-1 Aquatic		
Crustacea EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish LC50	Fathead Minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Propylene Glycol CAS # 57-55-6 Aquatic		
Crustacea EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish LC50	Fathead Minnow (Pimephales promelas)	710 mg/l, 96 hours

*Estimates for product may be based on additional component data not shown.

12.2 Persistence and Degradability

No data is available on the degradability of this product.

12.3 Bioaccumulative Potential

Partition Coefficient n-Octanol/Water (log Kow)	
Acetone	-0.24
Butyl Cellosolve/Glycol Ether EB	0.83
Methanol	-0.77
Propylene Glycol	-0.92

12.4 Mobility in Soil

No data available.

12.5 Other Adverse Effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

SECTION 13: Disposal considerations

13.1 Disposal Instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

13.2 Local Disposal Regulations

Dispose in accordance with all applicable regulations.

13.3 Hazardous Waste Code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

13.4 Waste from Residues/Unused Products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

13.5 Contaminated Packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

SECTION 14: Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

DOT	
UN Number	UN1263
UN Proper Shipping Name	Paint related material including paint thinning, drying, removing, or reducing compound
Transport Hazard Class(es) Class	3
Subsidiary Risk	-
Label(s)	3
Packing Group	II
Special Precautions for User	Read safety instructions, SDS and emergency procedures before handling.
Special Provisions	149*, B52, IB2, T4, TP1, TP8, TP28
Packaging Exception	150
Packaging Non Bulk	173
Packaging Bulk	242

IATA	
UN Number	UN1263
UN Proper Shipping Name	Paint related material (including paint thinning or reducing compounds)
Transport Hazard Class(es) Class	3
Subsidiary Risk	-
Packing Group	II
Environmental Hazards	No.
ERG Code	3L
Special Precautions for User	Read safety instructions, SDS and emergency procedures before handling.
Passenger and Cargo Aircraft	Allowed.
Cargo Aircraft Only	Allowed.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

IMDG	
UN Number	UN1263
UN Proper Shipping Name	PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
Transport Hazard Class(es) Class	3
Subsidiary Risk	-
Packing Group	II
Environmental Hazards: Marine Pollutant	No.
EmS	F-E, S-E
Special Precautions for User	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.

14.2 DOT



14.3 IATA; IMDG



SECTION 15: Regulatory information

15.1 US Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.

15.1.1 TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

15.1.2 CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) - Listed.

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2) - Listed.

Methanol (CAS 67-56-1) - Listed.

15.1.3 SARA 304 Emergency Release Notification

Not regulated.

15.1.4 OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

15.2 Superfund Amendments and Reauthorization Act of 1986 (SARA)

15.2.1 Hazard Categories

Immediate Hazard - Yes

Delayed Hazard - No

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

15.2.2 SARA 302 Extremely Hazardous Substance

Not listed.

15.2.3 SARA 311/312 Hazardous Chemical

No

15.2.4 SARA 313 (TRI reporting)

CHEMICAL NAME	CAS NUMBER	% BY WEIGHT
Butyl Cellosolve/Glycol Ether EB	111-76-2	0<5
Methanol	67-56-1	0<5

15.3 Other Federal Regulations

15.3.1 Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methanol (CAS 67-56-1)

15.3.2 Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

15.3.3 Safe Drinking Water Act (SDWA)

Not Regulated.

15.3.4 Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code

Acetone (CAS 67-64-1)	6532
-----------------------	------

15.3.5 Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35%WV
-----------------------	-------

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

15.3.6 DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
-----------------------	------

15.4 US State Regulations

15.4.1 US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

15.4.2 US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Methanol (CAS 67-56-1)

15.4.3 US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Methanol (CAS 67-56-1)

15.4.4 US. New Jersey Worker and Community Right-To-Know Act

Acetone (CAS 67-64-1)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Methanol (CAS 67-56-1)

Propylene Glycol (CAS 57-55-6)

15.4.5 US. Pennsylvania Worker and Community Right-To-Know Law

Acetone (CAS 67-64-1)

Butyl Cellosolve/Glycol Ether Eb (CAS 111-76-2)

Methanol (CAS 67-56-1)

Propylene Glycol (CAS 57-55-6)

15.4.6 US. Rhode Island RTK

Acetone (CAS 67-64-1)

Butyl Cellosolve/Glycol Ether EB (CAS 111-76-2)

Methanol (CAS 67-56-1)

15.4.7 US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

15.4.8 US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1) - Listed: March 16, 2012

Water Based Pre Clean (ONT.2975)

Safety Data Sheet ONT.2975

15.5 International Inventories

COUNTRY(S) OR REGION	INVENTORY NAME	ON INVENTORY (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

* A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION 16: Other information

16.1 Issue Date

06/02/2015

16.2 Version

01

16.3 Disclaimer

On Track Refinish Products cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.