



On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

Date of issue: 09/24/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	:	A-6040 Chip Guardian Silver, Aerosol
Product Description	:	Rocker Guard Coating, Silver, Aerosol Coating 405 g / 14.3 oz
General Use	:	Aerosol Coating, Automotive Use Only
Product Stock/Code	:	A-6040
Chemical Family	:	Organic Coating
Molecular Formula	:	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Supplier
MCGEHEE & MCGEHEE ENTERPRISES INC
120 SOUTH BOGGESS AVENUE
- USA
T (270) 338-4600 - F (270) 338-4602

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: Hazards identification

2.1 GHS Classifications

2.1.1 HEALTH:

Eye Irritation, Category 2
Skin Irritation, Category 2
Target Organ Toxicity (Single Exposure), Category 3
Target Organ Toxicity (Repeated Exposure), Category 2
Reproductive Toxicity, Category 2

2.1.2 PHYSICAL:

Flammable Aerosols, Category 1
Gases Under Pressure
Simply Asphyxiant, Category 1

2.2 GHS Label

Hazardous components for labelling:
ACETONE AND TOLUENE



On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

2.3 Signal Word

Danger

2.4 Hazard Statements

- H222: Extremely flammable aerosol.
- H280: Contains gas under pressure; may explode if heated.
- H319: Causes serious eye irritation.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H373: May cause damage to organs (central nervous system) through prolonged or repeated exposure.
- H361: Suspected of damaging fertility or the unborn child.
- H351: Suspected of causing cancer.
- H600: May displace oxygen and cause rapid suffocation.

2.5 Precautionary Statements

2.5.1 PREVENTION:

- P201: Obtain special instructions before use.
- P202: Do not handle until all safety precautions have been read and understood.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211: Do not spray on an open flame or other ignition source.
- P251: Do not pierce or burn, even after use.
- P264: Wash hands thoroughly after handling.
- P260: Do not breathe mist, vapors or spray.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves and eye protection.

2.5.2 RESPONSE

- P308+P313: IF exposed or concerned: Get medical advice/attention.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310: Immediately call a POISON CENTER or doctor/physician.
- P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.
- P332+P313: If skin irritation occurs: Get medical advice/attention.
- P362: Take off contaminated clothing.
- P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P312: Call a POISON CENTER or doctor/physician if you feel unwell.

2.5.3 STORAGE

- P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P403+P233: Store in a well-ventilated place. Keep container tightly closed.
- P405: Store locked up.

2.5.4 DISPOSAL

- P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

2.6 Emergency Overview

2.6.1 IMMEDIATE CONCERNS:

Flammable aerosol. Harmful if inhaled. Possible risk of harm to the unborn child. Causes serious eye irritation. Irritating to skin. Vapors may cause drowsiness and dizziness. Vapor reduces oxygen availability for breathing.

2.7 Hazards Not Otherwise Classified:

No data available.

2.8 Comments:

20 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity.
See sections 9 and 10 for more detailed information on physicochemical effects.
See section 11 for more detailed information on health effects.

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

See sections 12 for more detailed information on environmental effects.

This product is a consumer product and is labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations which take precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling. The actual container label will not include the above label elements. The labeling above applies to products used solely for industrial/professional use.

SECTION 3: Composition/Information on ingredients

Chemical Name	Wt. %	CAS No.
Acetone	40-45	67-64-1
Toluene	15-20	108-88-3
Propane	12-18	74-98-6
Isobutane	5-8	75-28-5
Aluminum, powder	3-5	7429-90-5

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

SECTION 4: First aid measures

4.1 Eye Contact

In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention, if irritation persists.

4.2 Skin Contact

Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated clothing and wash before reuse.

4.3 Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

4.4 Inhalation

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

4.5 Signs and Symptoms of Overexposure

4.5.1 EYE CONTACT:

Contact causes serious eye irritation. Symptoms may include pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

4.5.2 SKIN CONTACT:

Contact causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

4.5.3 INGESTION:

Substance may be harmful if swallowed. May cause irritation. Symptoms of ingestion may include abdominal pain, nausea, vomiting and diarrhea.

4.5.4 INHALATION:

High gas, vapor, mist or dust concentrations may be harmful if inhaled. May cause headaches and dizziness. High vapor concentrations may cause drowsiness. High vapor concentrations can displace oxygen in enclosed spaces and cause asphyxiation.

4.6 Notes to Physician

Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

ADDITIONAL INFORMATION:

No data available.

SECTION 5: Firefighting measures

5.1 Flammable Properties

Extremely flammable aerosol. Can readily form explosive mixtures at or above the flash point. Product can be ignited by static discharge.

5.2 Extinguishing Media

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

5.3 Hazardous Combustion Products

During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

5.4 Fire Fighting Procedures

Containers can build up pressure if exposed to heat (fire).

5.5 Fire Fighting Equipment

As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

5.6 Sensitivity to Static Discharge

Product is sensitive to static discharge.

5.7 Sensitivity to Mechanical Impact

Product is sensitive to mechanical impact. Do not puncture container. Contents under pressure. Do not expose to heat or store above 120 °F (49 °C).

SECTION 6: Accidental release measures

6.1 Small Spill

Eliminate all ignition sources. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly.

6.2 Environmental Precautions

Water Spill:

Do not flush to sewer.

Land Spill:

Avoid runoff into storm sewers and ditches which lead to waterways.

6.3 Special Protective Equipment

Clean up spills immediately, observing precautions in Protective Equipment section 8.

SECTION 7: Handling and storage

7.1 General Procedures

Comply with all national, state, and local codes pertaining to the storage, handling, dispensing, and disposal of flammable liquids.

7.2 Handling

Contents under pressure. Do not expose to heat or store above 120 °F (49 °C). Use only in a well ventilated area. Do not use in the presence of open flame or spark. Do not puncture container. Do not breathe vapors or spray mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

7.3 Storage

Keep away from heat and flame. Store in a cool dry place. Container may explode if heated. Do not incinerate.

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

SECTION 8: Exposure controls/personal protection

8.1 Exposure Guidelines

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

Chemical Name		Occupational Exposure Limits					
		OSHA PEL		ACGIH TLV		NIOSH REL	
		ppm	mg/m3	ppm	mg/m3	ppm	mg/m3
Acetone	TWA	1000	2400	500		250	590
	STEL			750		-	-
Toluene	TWA	200		50	188	100	375
	STEL	300				150	560
Propane	TWA	1000	1800	1000		1000	ND
Isobutane	TWA			1000		800	ND
Aluminum, powder	TWA		15T 5R		1		

8.2 Engineering Controls

Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

8.3 Personal Protective Equipment

8.3.1 EYES AND FACE:

Wear safety glasses with side shields (or goggles).

8.3.2 SKIN CONTACT:

Wear chemical resistant gloves.

8.3.3 RESPIRATORY:

NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

8.3.4 PROTECTIVE CLOTHING:

Not applicable of aerosol containers.

8.4 Work Hygienic Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid, without aerosol propellants
Odor	: Ketone
Odor Threshold	: No data available
Appearance	: Aerosol
Color	: Silver Grey
pH	: Not Applicable
% Volatiles	: 80 to 85 % w/w
Flash Point and Method	: -18 °C Setaflash Closed Cup (Acetone)
Flammable Limits	: 1.0 to 12.8
Notes: Based on data for acetone.	
Autoignition Temperature	: 480 °C
Notes: Based on data for acetone.	
Vapor Pressure	: 50 - 65 psig at 20 °C
Vapor Density	: > 1 (air=1)
Boiling Point	: 56 °C (Acetone)
Freezing Point	: No data available
Melting Point	: No data available
Solubility in Water	: Partial
Evaporation Rate (n-butyl acetate = 1)	: > 1
Density	: 0.97±0.02/ml at 20°C
Viscosity	: > 100 cps
VOC Content	: Summarized below
Partition Coefficient (n-octanol/water)	: No data available
Oxidizing Properties	: None

Comments:

9.2 Flammability Statement

The flammability of an aerosol is determined by its flame extension and/or flashback.

Flammability: Yes

Aerosol Flame Projection: > 15 cm but < 100 cm

Flashback: None

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

9.3 VOC Compliance Statement

Total Volatiles: < 660 g/l
80-85% w/w

VOC Regulation: USA National VOC Emission Standards for Aerosol Coatings - 40 CFR PART 59 SUBPART E

Coating Category: Flat Coatings

VOC Content: Product- Weighted Reactivity (PWR): <1.2 g O3/g product
< 40 % w/w (< 270 g/l)

The VOC content meets the 1.20 PWR category limit for Flat Coatings.

USA compliant.

SECTION 10: Stability and reactivity

10.1 Reactive Hazard

No

10.2 Hazardous Polymerization

Not expected to occur.

10.3 Stability

Stable.

10.4 Conditions to Avoid

Keep away from flames and any object that sparks. Container may explode if heated.

10.5 Possibility of Hazardous Reactions

Not Available.

10.6 Hazardous Decomposition Products

Carbon Monoxide and other toxic vapors.

10.7 Incompatible Materials

Oxidizing materials.

SECTION 11: Toxicological information

11.1 Product Acute Toxicity

Chemical Name	ORAL LD50 mg/kg (rat)	DERMAL LD50 mg/kg (rabbit)	INHALATION LC50 mg/l
Acetone	8400 5250 (mouse) 5300 (rabbit)	> 15,700	50.1 (rat;8h) 44.0 (mouse;4h)
Toluene	7000, 6400, 5500	12,270	49.0 (rat;4h) 30.0 (mouse;2h) 19.9 (mouse;7h)
Propane	Not Applicable	Not Applicable	>20,000 ppm (rat,4h)
Isobutane	Not Applicable	Not Applicable	142.5 ppm (rat,4h)

Acute Toxicity - Dermal LD50: The calculated ATE is > 2000 mg/kg.

Notes: Based on available data, the classification criteria for Acute Dermal Toxicity are not met for this mixture.

Acute Toxicity - Oral LD50: The calculated ATE is >2000 mg/kg.

Notes: Based on available data, the classification criteria for Acute Oral Toxicity are not met for this mixture.

Acute Toxicity - Inhalation LC50: The calculated ATE is >20 mg/l/4h (vapors) and >5 mg/l/4h (mists).

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

Notes: Based on available data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture.

11.2 Eye Irritation / Serious Eye Damage

Contains: Acetone. Contact causes serious eye irritation. The mixture is classified as: Eye Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as eye irritant, category 2). Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes.

11.3 Skin Irritation / Corrosion

Contains: Toluene. Causes skin irritation. The mixture is classified as: Skin Irritant, category 2, based on summation of ingredient data (>10% ingredients classified as skin irritant, category 2). Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

11.4 Carcinogenicity

Chemical Name	NTP Status	IARC Status	OSHA Status	Other
Acetone	—	—	—	
Toluene	—	3	—	—

Notes:

Based on available data, the classification criteria for Carcinogenicity are not met for this mixture (< 0.1% ingredients classified as a Carcinogen, category 1 or 2).

11.5 Specific Target Organ Toxicity - Repeated Exposure

The mixture is classified as: Specific Target Organ Toxicity - Repeated Exposure, category 2, based on ingredient data using the applicable cut-off/concentration limits ($\geq 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 2). Prolonged inhalation may be harmful. Chronic exposure to organic solvents such as Toluene have been associated with various neurotoxic effects including permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability, and loss of coordination. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

11.6 Respiratory / Skin Sensitizer

Based on available data, the classification criteria for skin/respiratory sensitization are not met of this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0 % ingredients classified as a skin/respiratory sensitizer, sub-category 1B).

11.7 Reproductive Toxicity

The mixture is classified as: Reproductive Toxicity, category 2 based on ingredient data using the applicable cut-off/concentration limits ($\geq 0.1\%$ ingredients classified as Reproductive Toxicity, category 2). May cause adverse reproductive effects. Possible risk of harm to the unborn child (Toluene).

11.8 Specific Target Organ Toxicity - Single Exposure

The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient data using the applicable cut-off/concentration limits ($\geq 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). Contains: Toluene. Can cause central nervous system depression (including unconsciousness). High vapor concentrations may cause drowsiness. May cause headaches and dizziness.

11.9 Germ Cell Mutagenicity

Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and <0.1% ingredients classified as Germ Cell Mutagen, category 2).

11.10 Aspiration Hazard

Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture (<10% ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity > 20.5 mm²/s at 40°C).

SECTION 12: Ecological information

12.1 Environmental Data

No data available.

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

12.2 Ecotoxicological Information

No data available.

12.3 Bioaccumulation/Accumulation

No data available.

12.4 Distribution

No data available.

12.5 Aquatic Toxicity (Acute)

No data available.

12.6 Chemical Fate Information

No data available.

SECTION 13: Disposal considerations

13.1 Disposal Method

Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

13.2 Product Disposal

When container is empty, press button to release all pressure, then dispose of container and unused contents in accordance with Local, Provincial/State and Federal regulations.

SECTION 14: Transport information

14.1 DOT (Department of Transportation)

Proper Shipping Name: Aerosols, Flammable

Primary Hazard Class/Division: 2.1

UN/NA Number: 1950

Packing Group: N/AP

Other Shipping Information: With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity as per DOT 173.306.

14.2 Air (ICAO/IATA)

Shipping Name: Aerosols, Flammable

UN/NA Number: 1950

Primary Hazard Class/Division: 2.1

Packing Group: N/AP

Subsidiary Risk: None

Label: Flammable Gas

14.3 Vessel (IMO/IMDG)

Shipping Name: Aerosols

UN/NA Number: 1950

Primary Hazard Class/Division: 2.1

Packing Group: N/AP

Marine Pollutant: None

Label: None

Note: With an inner packaging < 1.0 L, this product may be shipped as a Limited Quantity.

14.4 Canadian Transportation of Dangerous Goods Regulations

Shipping Name: Aerosols, Flammable

UN/NA Number: 1950

Primary Hazard Class/Division: 2.1

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

Packing Group: N/AP

TDG: With an inner packaging < 1.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

SECTION 15: Regulatory information

15.1 United States

15.1.1 SARA SECTION 311/312 HAZARD CATEGORIES

Fire Hazard: Yes

Sudden Release of Pressure: Yes

Reactive Hazard: No

Product Acute Toxicity: Yes

Product Chronic Toxicity: Yes

EPCRA SECTION 313 TOXIC CHEMICALS

Chemical Name	Wt. %	CAS No.
Toluene	15 - 20	108-88-3
Aluminum, powder	3 - 5	7429-90-5

EPCRA SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES

EPCRA Status:

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (RQ)

Chemical Name	Wt. %	RQ
Acetone	40 - 45	5,000
Toluene	15 - 20	1,000

TSCA (THE TOXIC SUBSTANCES CONTROL ACT)

TSCA Status:

All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112 (B) - HAZARDOUS AIR POLLUTANTS

Chemical Name	Wt. %	CAS No.
Toluene	15 - 20	108-88-3

CAA 112 (R) - LIST OF SUBSTANCES FOR ACCIDENTAL RELEASE PREVENTION

Name	CAS No.	Threshold Qty (TQ)
Propane	74-98-6	10,000
Butane	75-28-5	10,000

CALIFORNIA PROPOSITION 65

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

Chemical Name	Wt. %	Listed
Toluene	15 - 20	- Developmental Toxicity - Female Reproductive

OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

OSHA Status:

Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

15.9 CANADA

15.9.1 WHMIS Hazard Symbol and Classification:

See Section 2

15.9.2 WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

15.9.3 WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

Name	CAS No.	NPRI Part No.
Toluene	108-88-3	1A, 5 (VOC)
Propane	74-98-6	5 (VOC)
Butane (all isomers)	75-28-5	5 (VOC)

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments:

VOC Content — See Section 9.

SECTION 16: Other information

16.1 Reason for Issue

NEW

16.2 Approved By

Jim Gordon

16.3 Prepared By

Regulatory Compliance

16.4 Title

R&D Chemist

16.5 Date Prepared

09/24/2015


HMIS RATING

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		E

NFPA CODES



NFPA 30 / 30B Storage Classification:

Level 2 Aerosol

Manufacturer Supplemental Notes:

None

Data Sources:

Not Available.

Additional MSDS Information:

N/AV Not Available

N/AP Not Applicable

ND Not yet Determined

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Act

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

General Statements:

None

Comments:

None

Manufacturer Disclaimer:

On Track Chip Guardian (SILVER) (ONT.A-6040)

Safety Data Sheet ONT.A-6040

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.